

ISO 8041-2:2021 (E)

Human response to vibration — Measuring instrumentation — Part 2: Personal vibration exposure meters

Contents

| | |
|--------|--|
| | Foreword |
| | Introduction |
| 1 | Scope |
| 2 | Normative references |
| 3 | Terms and definitions |
| 4 | Reference environmental conditions |
| 5 | Performance specifications |
| 5.1 | General characteristics |
| 5.1.1 | Common characteristics |
| 5.1.2 | Special characteristics for whole-body vibration measurement |
| 5.1.3 | Special characteristics for hand-arm vibration measurement |
| 5.2 | Display |
| 5.3 | Electrical output |
| 5.4 | Vibration sensitivity |
| 5.5 | Accuracy of indication at reference frequency under reference conditions |
| 5.6 | Frequency weightings and frequency responses |
| 5.6.1 | Parameters |
| 5.6.2 | Band-limiting filter |
| 5.6.3 | a-v transition filter |
| 5.6.4 | Upward-step filter |
| 5.6.5 | Overall frequency weighting |
| 5.6.6 | Tolerances |
| 5.7 | Amplitude linearity |
| 5.8 | Instrument noise |
| 5.9 | Signal#burst response |
| 5.10 | Overload indication |
| 5.11 | Under#range indication |
| 5.12 | Time averaging |
| 5.13 | Running RMS acceleration |
| 5.14 | Clearance of data and instrument state (named reset) |
| 5.15 | Timing facilities |
| 5.16 | Electrical cross-talk |
| 5.17 | Vibration transducer characteristics |
| 5.18 | Power supply |
| 5.19 | Operator detection system |
| 5.20 | Detection of transient acceleration artefacts |
| 5.21 | Logging capabilities |
| 5.22 | Contact force measurement |
| 5.23 | Warning indication |
| 5.23.1 | General |
| 5.23.2 | Mandatory warning indications |
| 5.23.3 | Optional warning indications |
| 5.24 | Human interface and ergonomic aspects |
| 6 | Mounting |
| 7 | Environmental and electromagnetic criteria |

- 7.1 General
- 7.2 Air temperature
- 7.3 Surface temperature
- 7.4 Electrostatic discharge
- 7.5 Radio-frequency emissions and public-power-supply disturbances
- 7.6 Immunity to AC power-frequency fields and radio-frequency fields
- 7.7 Ingress of water and dust
- 8 Provision for use with auxiliary devices
- 9 Instrument marking
- 10 Instrument documentation
- 11 Performance testing
- 12 Pattern evaluation
 - 12.1 General
 - 12.2 Testing requirements
 - 12.3 Submission for testing
 - 12.4 Marking of the instrument and information in the instrument documentation
 - 12.5 Mandatory facilities and general requirements
 - 12.6 Initial instrument preparation
 - 12.7 Indication at the reference frequency under reference conditions
 - 12.8 Electrical cross-talk
 - 12.9 Vibration transducer
 - 12.10 Amplitude linearity
 - 12.10.1 Electrical tests of amplitude linearity
 - 12.10.2 Mechanical tests of amplitude linearity
 - 12.11 Frequency weightings and frequency responses
 - 12.11.1 General
 - 12.11.2 Mechanical tests of frequency response
 - 12.11.3 Electrical tests of frequency response
 - 12.11.4 Conformance
 - 12.12 Instrument noise
 - 12.13 Signal-burst response
 - 12.14 Overload indication
 - 12.15 Reset
 - 12.16 Combined axis outputs
 - 12.17 AC electrical output
 - 12.18 Timing facilities
 - 12.19 Power supply
 - 12.20 Environmental, electrostatic and radio-frequency tests
 - 12.20.1 General
 - 12.20.2 Expanded uncertainties for measurements of environmental conditions
 - 12.20.3 Acclimatization requirements for tests of the influence of air temperature and relative humidity
 - 12.20.4 Test of the influence of air temperature and relative humidity combined
 - 12.20.5 Influence of surface temperature
 - 12.20.6 Influence of electrostatic discharges
 - 12.20.7 Radio-frequency emissions and public-power-supply disturbances
 - 12.20.8 Immunity to AC power-frequency fields and radio-frequency fields
 - 12.21 Operator detection system
 - 12.22 Logging capabilities
 - 12.23 Warning indication (mandatory warnings)
 - 12.24 Test report
- 13 Periodic verification
 - 13.1 General
 - 13.2 Testing requirements
 - 13.3 Test object
 - 13.4 Submission for testing
 - 13.5 Preliminary inspection
 - 13.6 Marking of the instrument and information in the instrument documentation

| | |
|---------|--|
| 13.7 | Test procedure |
| 13.8 | Test parameters |
| 13.8.1 | Vibration measurement chain for hand-arm vibration |
| 13.8.2 | Vibration measurement chain for whole-body vibration |
| 13.8.3 | Vibration measurement chain low-frequency whole-body vibration |
| 13.9 | Conducting the test |
| 13.10 | Test report |
| 14 | In-situ check |
| 14.1 | General |
| 14.2 | Preliminary inspection |
| 14.3 | Vibration sensitivity (field calibration) |
| Annex A | (informative) Treatment of transient acceleration artefacts |
| A.1 | Identifying and dealing with artefacts |
| A.2 | Principles of artefact treatment |
| A.3 | Treatment of artefacts |
| A.3.1 | General |
| A.3.2 | Cutting out the artefact |
| A.3.3 | Linearizing the artefact |
| A.3.4 | Substituting the artefact |
| A.4 | Example of hand-arm artefact treatment |
| A.5 | Example of whole-body artefact treatment |
| Annex B | (informative) Influence of coupling force on hand-arm vibration evaluation |
| B.1 | General |
| B.2 | Measurement of coupling forces |
| Annex C | (informative) Human interface |

Page count: 53