

# ISO 21955:2021 (E)

## Acoustics — Experimental method for transposition of dynamic forces generated by an active component from a test bench to a receiving structure

---

### Contents

|         |  |
|---------|--|
|         | Foreword   |
|         | Introduction   |
| 1       | Scope  |
| 2       | Normative references   |
| 3       | Terms and definitions  |
| 4       | Principle of the method of transposition of the dynamic force      |
| 4.1     | General matters  |
| 4.2     | General formulae   |
| 4.3     | Geometrical considerations   |
| 5       | Operating mode   |
| 5.1     | General  |
| 5.2     | Synopsis of procedure  |
| 5.3     | Tasks and preliminary operations                                   |
| 5.4     | Transfer matrices determination                                    |
| 5.4.1   | General  |
| 5.4.2   | Final receiving structure transfer matrix determination Y RS       |
| 5.4.3   | Test bench transfer matrix determination, Y TB                     |
| 5.4.4   | Connecting device spring-like matrix properties determination, S I |
| 5.4.5   | Active Component transfer matrix determination, Y AC               |
| 5.5     | Measured dynamic forces transmitted to the test bench              |
| 5.6     | Predicted dynamic forces transmitted to the final structure        |
| 5.6.1   | General  |
| 5.6.2   | Strong decoupling  |
| 5.6.3   | Very similar bench and receiving structure                         |
| 5.6.4   | Case of a rigid receiving structure                                |
| 5.6.4.1 | General  |
| 5.6.4.2 | Rigid test bench (marble)  |
| 5.6.4.3 | Non-rigid test bench   |
| 5.6.5   | Case of a non-rigid receiving structure                            |
| 5.6.5.1 | General  |
| 5.6.5.2 | Rigid test bench (marble)  |
| 5.6.5.3 | Non-rigid test bench   |
| 5.6.5.4 | Evaluation of the quality of the predicted forces                  |
| 6       | Requirements for data in test report                               |
| 6.1     | Specification of the integrator to the supplier                    |
| 6.2     | Data sent by the supplier to the integrator                        |
| Annex A | (informative) Theoretical developments                             |
| A.1     | Introduction   |
| A.2     | Components formulae  |
| A.3     | Total system formulae  |
| A.4     | Transposition to dynamic forces                                    |
| Annex B | (informative) Frequency response functions measurement             |
| B.1     | General  |
| B.2     | Measurement of transfer functions a f <sup>-</sup>                 |

- B.2.1 Implementation and fixtures
- B.2.1.1 General
- B.2.1.2 Assembly 1 - One single 3D accelerometer by attachment point.
- B.2.1.3 Assembly 2 - Using multiple 3D anchor accelerometers by attachment point
- B.2.2 Recommendations

#### Annex C (informative) Dynamic forces measurement

- C.1 General
- C.2 Direct method by force sensor
  - C.2.1 Test set-up and fixture
  - C.2.2 Preliminary measurements of force/force transfers
    - C.2.2.1 General
    - C.2.2.2 Recommendations
    - C.2.2.3 Equipment used
- C.3 Indirect method: calculation from accelerometer measurements
  - C.3.1 Principle
  - C.3.2 Implementation and fixtures
    - C.3.2.1 Assembly 1
    - C.3.2.2 Assembly 2
    - C.3.2.3 Assembly 3
  - C.3.3 Recommendations
- C.4 Method of dynamic stiffness
  - C.4.1 Principle
  - C.4.2 Implementation and fixtures
  - C.4.3 Recommendations

#### Annex D (informative) Data processing

- D.1 General
- D.2 Direct measurement (see C.1)
- D.3 Indirect method (see C.2)
- D.4 Transfer matrices for dynamic force prediction

#### Annex E (informative) Study of a wiper system

- E.1 General description of the case study
- E.2 Transfer matrices measurement
- E.3 Direct measurement of the dynamic forces on test bench
- E.4 Validation of estimated dynamic forces on bench
- E.5 Estimated dynamic forces on vehicle
  - E.5.1 Prediction results
  - E.5.2 Validation of estimated dynamic force on bench

#### Annex F (informative) Equivalent force torsor and block-sensor method

- F.1 Description of the method
  - F.1.1 General
  - F.1.2 Theoretical principles
  - F.1.3 Smart receiver for identification – the “block-sensor”
  - F.1.4 Selection of measurement parameters
  - F.1.5 Equivalent coupling point and transfer matrix
    - F.1.5.1 Acceleration at the coupling equivalent coupling point  $\gamma C$ , matrix  $H v$
    - F.1.5.2 Force at the coupling equivalent coupling point  $F_{ecp}$
- F.2 Measurement procedure
  - F.2.1 General
  - F.2.2 Step 1: Suspend the receiver
  - F.2.3 Step 2: Sensor localization optimization and installation
  - F.2.4 Step 3: measurement of the receiver acceleration
  - F.2.5 Step 4: coupling of the source to the receiver
  - F.2.6 Step 5-6-7: Measurement of the assembly mobility
  - F.2.7 Step 8: Calculation of the active component mobility
  - F.2.8 Step 9: Measurement of the operational accelerations
  - F.2.9 Step 10: Calculation of blocked forces
- F.3 Autovalidation