

DIN ISO 16079-2:2022-06 (E)

Condition monitoring and diagnostics of wind turbines - Part 2: Monitoring the drivetrain (ISO 16079-2:2020)

Contents

Page

National foreword	4
National Annex NA (informative) Bibliography	5
Foreword	6
Introduction	7
1 Scope	10
2 Normative references	10
3 Terms and definitions	10
4 Abbreviated terms	11
5 Failure mode and symptoms analysis (FMSA)	11
5.1 General	11
5.2 The process of the FMSA analysis	11
6 Descriptors for fault detection	12
6.1 General	12
6.2 Descriptor types	13
6.3 Descriptors based on process parameters — Operational values	14
6.3.1 General	14
6.3.2 Measurement of process parameter descriptors	15
6.4 Measurement of rotational speed and descriptors based on rotational speed	15
6.4.1 General	15
6.4.2 Measurement of rotational speed	16
6.5 Descriptors based on vibration	16
6.5.1 References to other standards	16
6.5.2 General	16
6.5.3 Measurement of vibration	17
6.5.4 Transducers for vibration measurements	17
6.5.5 Vibration transducer mounting	18
6.6 Descriptors based on stress wave measurements	19
6.6.1 General	19
6.6.2 Measurement of stress waves	19
6.6.3 Transducers for stress wave measurement	20
6.6.4 Mounting of stress wave sensors	20
6.7 Descriptors based on oil debris in lubricant oil	20
6.7.1 General	20
6.7.2 Oil debris descriptors	21
6.7.3 Oil debris sensors	21
7 Descriptor monitoring interval	22
7.1 Reference to other standards	22
7.2 Factors influencing the monitoring interval	22

8	Descriptor notification criteria	23
8.1	Reference to other standards.....	23
8.2	General.....	23
8.3	Establishing descriptor alarm and alert limits for a new turbine.....	24
8.4	Establishing alarm and alert limits for a turbine in normal operating condition.....	24
8.5	Establishing alert limits upon component change.....	24
9	Handling changes in operating conditions — The operational state bin concept	25
9.1	General.....	25
9.2	Example of how to use active power as an operational state.....	25
10	Transducer locations	26
10.1	Reference to other standards and guidelines.....	26
10.2	Location of vibration transducers.....	26
10.3	Location of stress wave transducers.....	28
10.4	Location of oil debris sensors.....	28
10.5	Example of naming conventions and transducer locations.....	28
11	Baseline — Initial recording of data for diagnosis at commissioning time	29
11.1	General.....	29
11.2	Duration of time waveforms for baseline recording.....	29
11.3	Repeatability and stability of time waveform recordings.....	30
11.4	Sampling rate of time waveform for baseline recording.....	30
11.5	Initial check of the baseline data — Recommendations.....	30
12	Diagnosis of faults and their causes	31
12.1	Reference to other standards.....	31
12.2	General.....	31
12.3	Component data.....	31
12.4	Raw-data time waveforms for detailed diagnosis.....	31
12.5	Regular recording.....	31
12.6	Recording on request.....	32
13	Prognosis	32
13.1	Reference to other standards.....	32
13.2	General.....	32
13.3	Type I — Failure data-based prognostics — Statistically based.....	33
13.4	Type II — Stress based prognostics — Model based.....	34
13.5	Type III — Data-driven method — Condition based.....	34
14	Review of the condition monitoring and diagnosis system design	34
14.1	Reference to other standards.....	34
14.2	General.....	35
14.3	Assessment of effectiveness of the condition monitoring system.....	35
14.4	Cost benefit analysis.....	36
	14.4.1 General.....	36
	14.4.2 Simple model.....	36
	14.4.3 Advanced model.....	37
	Annex A (informative) Details on vibration-based descriptor types	40
	Annex B (informative) FMSA analysis of the drivetrain	49
	Bibliography	52