

# DIN EN ISO 20270:2023-12 (E)

## Acoustics - Characterization of sources of structure-borne sound and vibration - Indirect measurement of blocked forces (ISO 20270:2019)

---

<b>Contents</b>		<b>Page</b>
<b>European foreword</b>		<b>3</b>
<b>Foreword</b>		<b>4</b>
<b>Introduction</b>		<b>5</b>
<b>1 Scope</b>		<b>7</b>
<b>2 Normative references</b>		<b>7</b>
<b>3 Terms and definitions</b>		<b>7</b>
<b>4 Selection of degrees of freedom (DOFs)</b>		<b>12</b>
4.1	General	12
4.2	Source receiver interface	13
4.3	Contact DOFs	13
4.4	Indicator DOFs	13
4.4.1	General	13
4.4.2	All indicator DOFs at contact area	14
4.4.3	No indicator DOF at contact area	14
4.4.4	Some indicator DOFs at contact area	14
4.5	Validation DOFs	14
<b>5 Test arrangement</b>		<b>14</b>
5.1	General	14
5.2	Representativeness of the receiver	14
5.3	Design of test receiver	15
5.4	Avoidance of secondary noise sources	15
<b>6 Measuring equipment</b>		<b>16</b>
6.1	General	16
6.2	Multi-channel analyser	16
6.3	Vibration sensors	16
6.4	Means of excitation	16
<b>7 Test procedure</b>		<b>16</b>
7.1	General	16
7.2	Operational test	18
7.3	Frequency response function (FRF) test	18
7.3.1	General	18
7.3.2	Direct FRF measurement	18
7.3.3	Reciprocal FRF measurement	18
7.4	Preliminary test with artificial excitation	19
<b>8 Analysis procedure</b>		<b>19</b>
<b>9 Uncertainties and validation</b>		<b>20</b>
9.1	General	20
9.2	On-board validation	21
9.3	Preliminary validation using artificial excitation	21
<b>10 Test report</b>		<b>21</b>
<b>Annex A (informative) Example of a test report: Electric rear axle drive in a passenger car; transfer path analysis (TPA) and estimation of blocked forces in situ according to ISO 20270:2019</b>		<b>23</b>
<b>Annex B (informative) Tests for validity of measurement data</b>		<b>30</b>
<b>Annex C (informative) Case studies</b>		<b>32</b>
<b>Annex D (informative) Criteria for selection of indicator and validation DOFs</b>		<b>37</b>
<b>Annex E (informative) Prediction of sound and vibration</b>		<b>41</b>
<b>Bibliography</b>		<b>43</b>