

DIN EN ISO 5349-3:2026-03 (E)

Mechanical vibration - Measurement and evaluation of human exposure to hand-transmitted vibration - Part 3: Isolated and repeated shocks using the frequency range of ISO 5349-1 (ISO 5349-3:2025)

| Contents | Page |
|---|-------------|
| Foreword | iv |
| Introduction | v |
| 1 Scope | 1 |
| 2 Normative references | 1 |
| 3 Terms and definitions | 1 |
| 4 Symbols and abbreviated terms | 2 |
| 5 Hand-transmitted shock | 3 |
| 6 Measurement and evaluation | 4 |
| 6.1 Evaluation of continuous hand-transmitted vibration..... | 4 |
| 6.2 Frequency range and frequency weightings..... | 4 |
| 6.3 Evaluation of HTS..... | 5 |
| 6.4 Measuring HTS..... | 5 |
| 6.4.1 General..... | 5 |
| 6.4.2 Location and orientation of transducers..... | 5 |
| 6.4.3 Determining the instantaneous total values..... | 5 |
| 6.4.4 Transducer coupling..... | 6 |
| 6.4.5 Sampling..... | 7 |
| 6.4.6 Measurement period..... | 7 |
| 7 Application of HTS evaluations | 8 |
| 7.1 Emission information..... | 8 |
| 7.2 Health effects..... | 8 |
| 8 Test report | 8 |
| Annex A (informative) Isolated and continuous hand-transmitted shock | 9 |
| Annex B (informative) Examples of VPM, p_F measured on common machine types | 14 |
| Annex C (informative) Supplementary measurement parameters | 15 |
| Bibliography | 20 |