

# ISO 16063-22:2005-06 (E)

## Methods for the calibration of vibration and shock transducers - Part 22: Shock calibration by comparison to a reference transducer

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>2</b>
<b>4</b>	<b>Uncertainty of measurement .....</b>	<b>2</b>
<b>5</b>	<b>Apparatus .....</b>	<b>3</b>
5.1	General considerations .....	3
5.2	Anvil shock calibrators (100 m/s <sup>2</sup> to 100 km/s <sup>2</sup> ) .....	3
5.3	Hopkinson bar shock calibrators .....	8
5.4	Oscilloscope .....	9
5.5	Waveform recorder with computer interface .....	9
5.6	Computer with data-processing capability .....	10
5.7	Filters .....	10
5.8	Other requirements .....	10
<b>6</b>	<b>Ambient conditions .....</b>	<b>10</b>
<b>7</b>	<b>Preferred accelerations and pulse durations .....</b>	<b>10</b>
<b>8</b>	<b>Method .....</b>	<b>11</b>
8.1	Test procedure .....	11
8.2	Data acquisition .....	11
8.3	Signal processing .....	11
<b>9</b>	<b>Reporting the calibration results .....</b>	<b>15</b>
<b>Annex A (normative) Expression of uncertainty of measurement in calibration .....</b>		<b>16</b>
<b>Annex B (informative) Uncertainty examples -- Expression of uncertainty of measurement in calibration .....</b>		<b>19</b>
<b>Bibliography .....</b>		<b>22</b>