ISO 10848-1:2006-04 (E)

Acoustics - Laboratory measurement of the flanking transmission of airborne and impact sound between adjoining rooms - Part 1: Fr ame document

Contents

Page

Foreword iv

1 Scope 1

2 Normative references 1

3 Terms and definitions 2

4 Quantities to characterize flanking transmission 6
4.1 General 6
4.2 Normalized flanking level difference Dn,f and normalised flanking impact sound pressure level Ln,f 6
4.3 Vibration reduction index, Kij 6
4.4 Selection of the principle of measurement 8

5 Measuring equipment 9

6 General requirements for test specimens and test rooms 9

7 Measurement methods 10
7.1 Measurement of Dn,f and Ln,f 10
7.2 Measurement of the vibration reduction index with structure-borne excitation 12
7.3 Measurement of the structural reverberation time 15
7.4 Measurement of the vibration reduction index with airborne excitation 16
7.5 Frequency range of measurement 17

8 Influences from the structures of the test facility 17
8.1 Criterion to verify flanking transmissions through constructions of the test facility 17
8.2 Conventional limit for light elements compared with the surrounding elements of the test facility 18
8.3 Verification procedure for a light flanking element that is structurally independent of a separating element 18

9 Shielding 18

Annex A (normative) Single-number rating of the vibration reduction index 24

Bibliography 25