ISO/TS 4869-5:2006-10 (E)

Acoustics - Hearing protectors - Part 5: Method for estimation of noise reduction using fitting by inexperienced test subjects

Contents

Page

Foreword v

Introduction vii

1 Scope 1

2 Normative references 1

3 Terms and definitions 2

4 Measurement of the noise reduction of hearing protectors 3
4.1 Test signals 3
4.2 Test site 3
4.2.1 Conditions to be met for the test to be valid 3
4.2.2 Reverberation time 4
4.2.3 Background noise 4
4.3 Test equipment 5

5 Test subjects 6
5.1 Conditions for subject acceptance/dismissal 6
5.1.1 General 6
5.1.2 Age and sex 6
5.1.3 Previous experience with hearing protectors 7
5.1.4 Anatomical features 7
5.1.5 Maximum hearing threshold levels 7
5.1.6 Minimum hearing threshold levels 7
5.1.7 Literacy 7
5.1.8 Threshold variability 7
5.2 Number of subjects 7
5.3 Otoscopic inspection 8
5.4 Spectacles and jewellery 8
5.5 Maximum number of tests per subject 8
5.6 Exceptions 8

6 Product samples 8
6.1 General 8
6.2 Custom-moulded ear-plugs 8
6.3 Special requirements for product instruction 8
6.4 Variable position headbands 9
6.5 Variable band force 9

7 Test procedure 9
7.1 Number of open-ear and occluded-ear threshold measurements 9
7.2 Information to subjects 9
7.3 Prior to entering the test room 10
7.4 Inside the test room 10
7.4.1 Positioning the subject 10
7.4.2 Quiet period prior to first threshold determination 11
7.4.3 Fitting the hearing protector for test 11
7.4.4 Re-determination of thresholds 11

8 Computation of noise reduction values 12
8.1 General 12
8.2 Calculation of the individual noise reductions 12
8.3 Calculation of group noise reduction 12
8.4 Uncertainty of the noise reduction data 13

9 Reporting of data 13

Annex A (informative) Uncertainty of hearing protector noise reduction measurements 15

Bibliography 18