

ISO 10303-111:2007-05 (E)

Industrial automation systems and integration - Product data representation and exchange - Part 111: Integrated application resource: Elements for the procedural modelling of solid shapes

Contents

	Page
1 Scope	1
2 Normative references	2
3 Terms, definitions and abbreviations	2
3.7 Other terms and definitions	4
3.8 Abbreviations	4
4 Solid shape element	5
4.1 Introduction	5
4.2 Fundamental concepts and assumptions	6
4.3 Solid shape element type definitions	7
4.3.1 base solid select	7
4.3.2 blend end condition select	8
4.3.3 generalized surface select	8
4.3.4 trim condition select	9
4.3.5 blend radius variation type	9
4.3.6 trim intent	9
4.4 Solid shape element entity definitions	10
4.4.1 modified solid	10
4.4.2 edge blended solid	11
4.4.3 track blended solid	12
4.4.4 track blended solid with end conditions	13
4.4.5 solid with constant radius edge blend	15
4.4.6 solid with variable radius edge blend	17
4.4.7 solid with chamfered edges	20
4.4.8 solid with single offset chamfer	21
4.4.9 solid with double offset chamfer	21
4.4.10 solid with angle based chamfer	22
4.4.11 surfaced open shell	24
4.4.12 sculptured solid	25
4.4.13 sculptured solid with selection	26
4.4.14 offset face solid	27
4.4.15 shelled solid	28
4.4.16 double offset shelled solid	30
4.4.17 complex shelled solid	31
4.4.18 modified solid with placed configuration	31
4.4.19 solid with depression	32
4.4.20 solid with through depression	33
4.4.21 solid with hole	34
4.4.22 solid with stepped round hole	34
4.4.23 conical stepped hole transition	35
4.4.24 solid with stepped round hole and conical transitions	37
4.4.25 solid with flat bottom round hole	38
4.4.26 solid with spherical bottom round hole	39
4.4.27 solid with conical bottom round hole	40
4.4.28 solid with pocket	41
4.4.29 solid with rectangular pocket	42
4.4.30 solid with circular pocket	44

4.4.31	solid with general pocket	45
4.4.32	solid with slot	46
4.4.33	solid with straight slot	47
4.4.34	solid with curved slot	49
4.4.35	solid with trapezoidal section slot	49
4.4.36	solid with tee section slot	50
4.4.37	solid with groove	52
4.4.38	solid with protrusion	54
4.4.39	solid with circular protrusion	54
4.4.40	solid with rectangular protrusion	55
4.4.41	solid with general protrusion	56
4.4.42	solid with shape element pattern	56
4.4.43	solid with circular pattern	57
4.4.44	solid with rectangular pattern	59
4.4.45	solid with incomplete circular pattern	60
4.4.46	solid with incomplete rectangular pattern	61
4.4.47	thickened face solid	62
4.4.48	extruded face solid with trim conditions	64
4.4.49	extruded face solid with draft angle	67
4.4.50	extruded face solid with multiple draft angles	67
4.4.51	revolved face solid with trim conditions	68
4.4.52	auxiliary geometric instance aggregator	70
4.5	Solid shape element function definitions	71
4.5.1	check continuous edges	71
4.5.2	compute total depth	72
4.5.3	validate countersink radii	73
Annex A (normative) Short names of entities		75
Annex B (normative) Information object registration		77
B.1	Document identification	77
B.2	Schema identification	77
Annex C (informative) Computer interpretable listings		78
Annex D (informative) EXPRESS-G diagrams		79
E.1	Representation of constructional operations	91
E.2	Representation of local shape configurations	92
Bibliography		93
Index		94
Figures		
Figure 1 Schema level diagram of relationships between the solid - shape element schema		16
Figure 2 L-section block		16
Figure 3 L-section block of Figure 2 with constant radius edge blend		16
Figure 4 A track blended solid with a constant radius edge blend		17
Figure 5 L-section block of Figure 2 with variable radius edge blend		19
Figure 6 A track blended solid with end conditions for which the blend radius is variable		19
Figure 7 Solid with double offset chamfer		22
Figure 8 Solid with angle based chamfer		24
Figure 9 Solid and generalized surface defining a sculptured solid		26

Figure 10 The sculptured solid after the partitioning operation	26
Figure 11 Offset face solid	28
Figure 12 Shelled solid	30
Figure 13 Cross-section of solid with stepped round hole	36
Figure 14 Cross-section of solid with stepped round hole and conical transitions	38
Figure 15 Bottom conditions for blind round holes	41
Figure 16 Solid with rectangular pocket	44
Figure 17 Solid with straight slot, having two closed ends	48
Figure 18 Straight slot with multiple entries and exits from part material	48
Figure 19 Trapezoidal and T slot sections	51
Figure 20 Solid with groove	53
Figure 21 The effect of radial alignment in solid with circular pattern	58
Figure 22 Solid with rectangular pattern	60
Figure 23 Solid with incomplete circular pattern	61
Figure 24 Solid with incomplete rectangular pattern	62
Figure 25 Thickened face solid	63
Figure 26 Extruded face solid with draft angle	66
Figure D.1 solid shape element schema - EXPRESS-G diagram 1 of 11	80
Figure D.2 solid shape element schema - EXPRESS-G diagram 2 of 11	81
Figure D.3 solid shape element schema - EXPRESS-G diagram 3 of 11	82
Figure D.4 solid shape element schema - EXPRESS-G diagram 4 of 11	83
Figure D.5 solid shape element schema - EXPRESS-G diagram 5 of 11	84
Figure D.6 solid shape element schema - EXPRESS-G diagram 6 of 11	85
Figure D.7 solid shape element schema - EXPRESS-G diagram 7 of 11	86
Figure D.8 solid shape element schema - EXPRESS-G diagram 8 of 11	87
Figure D.9 solid shape element schema - EXPRESS-G diagram 9 of 11	88
Figure D.10 solid shape element schema - EXPRESS-G diagram 10 of 11	89
Figure D.11 solid shape element schema - EXPRESS-G diagram 11 of 11	90
Tables A.1 Short names of entities	75