

DIN EN 13035-2:2008-06 (E)

Machines and plants for the manufacture, treatment and processing of flat glass - Safety requirements - Part 2: Storage, handling and transportation equipment outside the factory

Contents	Page
Foreword	4
Introduction	5
1 Scope	6
2 Normative references	6
3 Terms and definitions	7
3.1 General definitions	7
3.2 Definitions concerning equipment	8
4 List of significant hazards	9
4.1 General	9
4.2 During transportation	9
4.3 During loading and unloading	10
4.4 Flat glass transport by in-loader	11
5 Safety requirements and/or protective measures	11
5.1 General	11
5.2 General requirements	12
5.3 Angle of lean	12
5.4 Glass-retaining systems	12
5.5 Bearers and cladding materials	13
5.6 Special transport systems	13
5.6.1 In-loader vehicle	13
5.6.2 Frail on truck and van	15
5.6.3 Stillages and pallets	15
5.7 Vacuum lifting device	15
6 Verification of safety requirements and/or protective measures	15
7 Information for use	16
7.1 General	16
7.2 Signals and warning devices	16
7.3 Accompanying documents	16
7.4 Marking	17
Annex A (informative) Types of equipment	18
Annex B (informative) Guidelines for the glass-retention devices	21
B.1 Hydraulic and pneumatic supports	21
B.2 Air bags/cushions	21
B.3 Stanchions for supports on frails	21
B.4 Protection of the belt against glass impacts by means of an edge protection	21
B.5 Straps	21
Annex C (informative) Symbols for labels and signs	22

Annex ZA (informative) Relationship between this European Standard and the Essential Requirements of EU-Directive 98/37/EC	23
Annex ZB (informative) Relationship between this European Standard and the Essential Requirements of EU Directive 2006/42/EC	24
Bibliography	25
Figures Figure A.1 -- Frail, fitted to a van	18
Figure A.2 -- Frail with a changeable angle of lean	19
Figure A.3 -- Frail with movable feet to secure the angle of lean during loading/unloading	19
Figure A.4 -- In-loader vehicle	20
Figure C.1 -- Warning of hand injuries	22
Figure C.2 -- Trespassing prohibited	22
Tables Table 1	9
Table 2	10
Table 3	11
Table 4	16