

DIN ISO 8132:2008-06 (E)

Hydraulic fluid power - Single rod cylinders, 16 MPa (160 bar) medium and 25 MPa (250 bar) series - Mounting dimensions for accessories (ISO 8132:2006)

Contents		Page
National foreword		3
Introduction		4
1	Scope	5
2	Normative references	6
3	Terms and definitions	6
4	Mounting dimensions	6
5	Material -- Load capacity	6
6	Application instructions	6
6.1	Installation	6
6.2	Lubrication	6
7	Designation	7
8	Identification statement (Reference to this International Standard)	7
Figures Figure 1 -- AP2 -- Rod clevis, female thread		8
Figure 2 -- AF3 -- Rod flange, circular		9
Figure 3 -- AB4 -- Clevis bracket, straight		10
Figure 4 -- AB3 -- Clevis bracket, in angle		11
Figure 5 -- AT4 - Trunnion bracket		12
Figure 6 -- AA8 -- Pivot pin, plain or spherical bearing (cotter pin or snap ring type)		13
Figure 7 -- AP6 -- Rod eye spherical, female thread		14
Figure 8 -- AP4 -- Rod eye plain, female thread		15
Tables Table 1 -- Dimensions of AP2 -- Rod clevis, female thread		8
Table 2 -- Dimensions of AF3 -- Rod flange, circular		9
Table 3 -- Dimensions of AB4 -- Clevis bracket, straight		10
Table 4 -- Dimensions of AB3 -- Clevis bracket, in angle		11
Table 5 -- Dimensions of AT4 - Trunnion bracket		12
Table 6 -- Dimensions of AA8 -- Pivot pin, plain or spherical bearing (cotter pin or snap ring type) ...		13
Table 7 -- Dimensions of AP6 -- Rod eye spherical, female thread		14
Table 8 -- Dimensions of AP4 -- Rod eye plain, female thread		15