

DIN ISO 6022:2008-06 (E)

Hydraulic fluid power - Mounting dimensions for single rod cylinders, 25 MPa (250 bar) series (ISO 6022:2006)

Contents		Page
National foreword		2
National Annex NA (informative) Bibliography		3
Introduction		4
1	Scope	5
2	Normative references	5
3	Terms and definitions	6
4	Dimensions	6
5	Bore sizes	6
6	Mounting types	6
7	Piston rod characteristics	7
8	Identification statement (reference to this International Standard)	7
Bibliography		17
Figures Figure 1 -- General dimensions		8
Figure 2 -- MF3 -- Head, circular flange and MF 4 -- Cap, circular flange		10
Figure 3 -- MP3 -- Cap, fixed plain eye, MP4 -- Cap, detachable plain eye, MP5 -- Cap, fixed eye with spherical bearing and MP6 -- Cap, detachable eye with spherical bearing		12
Figure 4 -- MT4 -- Intermediate fixed or movable trunnion (male)		14
Tables Table 1 -- General dimensions		9
Table 2 -- Dimensions of circular flange mountings MF3 and MF4		11
Table 3 -- Dimensions of cap eye mountings MP3, MP4, MP5 and MP6		13
Table 4 -- Dimensions of intermediate male trunnion mounting MT4		14
Table 5 -- Port and flange sizes		15
Table 6 -- Tolerances for mounting dimensions that are dependent on stroke		16
Table 7 -- Tolerances on piston stroke		16