

ISO 6396:2008-03 (E)

Earth-moving machinery - Determination of emission sound pressure level at operator's position - Dynamic test conditions

| Contents | | Page |
|--|---|-------------|
| Foreword | | iv |
| Introduction | | v |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 1 |
| 4 | Instrumentation | 2 |
| 5 | Test environment | 2 |
| 6 | Measurement of time-averaged A-weighted sound pressure levels | 2 |
| 6.1 | Operator stature | 2 |
| 6.2 | Operator presence | 2 |
| 6.3 | Microphone | 2 |
| 7 | Set-up and operation of machine, and operator's position set-up | 3 |
| 7.1 | Set-up and operation of machine | 3 |
| 7.2 | Setting-up operator's position for machines with cab | 4 |
| 8 | Acoustic measurements | 4 |
| 8.1 | Measurement procedure | 4 |
| 8.2 | Determination of measurement result | 4 |
| 9 | Information to be recorded | 4 |
| 10 | Information to be reported | 5 |
| 10.1 | Information | 5 |
| 10.2 | Declaration of sound emission data and uncertainty | 6 |
| Annex A (normative) Declaration of sound emission data and uncertainty | | 7 |
| Bibliography | | 8 |