

# ISO 6099:2009-04 (E)

## Fluid power systems and components - Cylinders - Identification code for mounting dimensions and mounting types

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
Introduction .....		v
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>1</b>
<b>4</b>	<b>Identification code for rod end types .....</b>	<b>1</b>
<b>4.1</b>	<b>Reference points and letter codes .....</b>	<b>1</b>
<b>4.1.1</b>	<b>General .....</b>	<b>1</b>
<b>4.1.2</b>	<b>Plain rod end .....</b>	<b>2</b>
<b>4.1.3</b>	<b>Pin rod end .....</b>	<b>2</b>
<b>4.1.4</b>	<b>Female threaded rod end .....</b>	<b>2</b>
<b>4.1.5</b>	<b>Male threaded rod end .....</b>	<b>3</b>
<b>4.1.6</b>	<b>Wrench flat piston rod end or hook wrench holes .....</b>	<b>4</b>
<b>4.1.7</b>	<b>Flanged piston rod end -- Alternative reference points .....</b>	<b>5</b>
<b>4.2</b>	<b>Identification code .....</b>	<b>5</b>
<b>5</b>	<b>Letter code for identifying cylinder mounting, envelope and accessory dimensions .....</b>	<b>6</b>
<b>5.1</b>	<b>General .....</b>	<b>6</b>
<b>5.2</b>	<b>Letter Z .....</b>	<b>6</b>
<b>5.3</b>	<b>Letter U .....</b>	<b>6</b>
<b>5.4</b>	<b>Letters W, X, Y, Z .....</b>	<b>6</b>
<b>5.5</b>	<b>Signs .....</b>	<b>6</b>
<b>5.6</b>	<b>Dimensioning .....</b>	<b>6</b>
<b>6</b>	<b>Identification code for mounting types .....</b>	<b>8</b>
<b>6.1</b>	<b>General .....</b>	<b>8</b>
<b>6.2</b>	<b>Mounting types .....</b>	<b>8</b>
<b>6.3</b>	<b>Letter codes of mounting and envelope dimensions according to cylinder mounting type .....</b>	<b>11</b>
<b>7</b>	<b>Identification code for accessory types .....</b>	<b>36</b>
<b>7.1</b>	<b>General .....</b>	<b>36</b>
<b>7.2</b>	<b>Accessory types .....</b>	<b>37</b>
<b>7.3</b>	<b>Letter codes of accessories according to accessory type .....</b>	<b>38</b>
<b>8</b>	<b>Designation of the position of the ports in round and square types .....</b>	<b>45</b>
<b>9</b>	<b>Identification statement (Reference to this International Standard) .....</b>	<b>46</b>