

DIN EN 1539:2010-04 (E)

Dryers and ovens, in which flammable substances are released - Safety requirements

Contents		Page
Foreword		4
Introduction		5
1 Scope		6
2 Normative references		6
3 Terms and Definitions		8
4 Significant hazards		12
5 Safety requirements and/or protective measures		17
5.1 General		17
5.2 Safety requirements against mechanical hazards		18
5.2.1 Shearing, crushing, drawing-in		18
5.2.2 Means of escape		18
5.2.3 Safety requirements against slip and fall hazards		19
5.3 Safety requirements against electrical hazards		19
5.3.1 General		19
5.3.2 Electrical equipment		19
5.3.3 External influences on the electrical equipment		19
5.4 Safety requirements against thermal hazards		19
5.5 Safety requirements against hazards from noise		20
5.6 Safety requirements against hazards from radiation		20
5.7 Safety requirements against hazards generated from hazardous substances		21
5.8 Fire protection and prevention		21
5.8.1 General		21
5.9 Explosion protection and prevention requirements		22
5.9.1 Type A-dryers		22
5.9.2 Type B-dryers		29
5.10 Control systems		31
5.11 Failure of energy supply		31
6 Verification of the safety requirements and/or measures		31
7 Information for use		34
7.1 General		34
7.2 Instruction handbook		34
7.2.1 General		34
7.2.2 Information related to installation		35
7.2.3 Information related to operation		35
7.2.4 Information related to maintenance and inspection		36
7.3 Marking		37
Annex A (normative) Basis for air flow calculation of chamber dryers and continuous flow dryers ..		38
A.1 Chamber dryers		38
A.1.1 Calculation basis for chamber dryers		38
A.2 Continuous flow dryers		43
A.2.1 Calculation basis for continuous flow dryers		43
A.2.2 Calculation basis for continuous flow dryers for powder coatings		45

Annex B (informative) Examples of calculation	46
B.1 Chamber dryers	46
B.1.1 Example 1: Calculation of the required minimum exhaust flow (see 3.20)	46
B.1.2 Example 2: Calculation of the maximum admissible amount of varnish	47
B.2 Continuous flow dryers	48
DIN EN 1539:2010-04 EN 1539:2009 (E) B.2.1 Examples for the calculation of the minimum exhaust flow rate	48
B.2.2 Example for the calculation of the maximum admissible throughput of flammable substances	50
Annex C (normative) Concentration measurement in dryers	52
C.1 General	52
C.2 Requirements for concentration measuring systems	52
C.3 Calculation of the lower explosion limit at drying temperature	53
C.3.1 Influence of temperature on the indicated value of concentration (physical influence)	53
C.3.2 Influence of the temperature of mixture on the kinetics of reaction (chemical influence) ..	54
C.3.3 Consideration of chemical and physical influences	54
Annex D (normative) Explosion reliefs	55
Annex ZA (informative) Relationship between this European Standard and the Essential Requirements of EU Directive Machinery 98/37/EC	56
Annex ZB (informative) Relationship between this European Standard and the Essential Requirements of EU Directive 2006/42/EC	57
Bibliography	58
Figures Figure 1 -- Maximum admissible concentration of flammable substances and admissible operating ranges for dryers with limited concentration	28
Figure A.1 -- Dependency of versus	42
Tables Table 1 -- List of significant hazards	12
Table 2 -- Requirements according to the operating ranges	27
Table 3 -- Verification	32