

# ISO 27894:2009-12 (E)

## Vacuum technology - Vacuum gauges - Specifications for hot cathode ionization gauges

---

| <b>Contents</b>    |  | <b>Page</b> |
|--------------------|--|-------------|
| Foreword .....     |  | iv          |
| Introduction ..... |  | v           |
| 1                  | <b>Scope .....</b>   | <b>1</b>    |
| 2                  | <b>Normative references .....</b>  | <b>1</b>    |
| 3                  | <b>Terms and definitions .....</b>   | <b>2</b>    |
| 4                  | <b>Symbols and abbreviated terms .....</b>   | <b>6</b>    |
| 5                  | <b>Principle of hot cathode ionization gauge .....</b>   | <b>7</b>    |
| 6                  | <b>Specifications for hot cathode ionization gauge to be provided by manufacturers .....</b>                       | <b>7</b>    |
| 7                  | <b>Additional (optional) specifications for hot cathode ionization gauge to be provided by manufacturers .....</b> | <b>10</b>   |
| 8                  | <b>Influences contributing to the measurement uncertainty with hot cathode ionization gauges .....</b>             | <b>11</b>   |
|                    | <b>Annex A (informative) Typical Bayard-Alpert gauge with a glass envelope .....</b>                               | <b>14</b>   |
|                    | <b>Annex B (informative) Typical electrical connection of a Bayard-Alpert gauge .....</b>                          | <b>15</b>   |
|                    | <b>Annex C (informative) Problems with ionization gauges .....</b>   | <b>16</b>   |
|                    | <b>Bibliography .....</b>  | <b>18</b>   |