

DIN EN 1804-3:2010-05 (E)

Machines for underground mines - Safety requirements for hydraulic powered roof supports - Part 3: Hydraulic control systems (includes Amendment A1:2010)

| Contents | | Page |
|--------------------|--|-------------|
| Foreword | | 4 |
| Introduction | | 5 |
| 1 | Scope | 6 |
| 2 | Normative references | 6 |
| 3 | Terms and definitions | 7 |
| 4 | List of hazards | 8 |
| 5 | Safety requirements | 10 |
| 5.1 | General requirements | 10 |
| 5.1.1 | General | 10 |
| 5.1.2 | Hazard areas | 10 |
| 5.1.3 | Arrangement of the control devices | 10 |
| 5.1.4 | Dead man's control | 10 |
| 5.1.5 | Automatic hydraulic control system | 10 |
| 5.1.6 | Automatic guaranteed setting control | 10 |
| 5.1.7 | Shut-off devices | 10 |
| 5.1.8 | Pressure indicator | 10 |
| 5.1.9 | Pipe and hose assemblies | 10 |
| 5.1.10 | Hydraulic fluids | 11 |
| 5.1.11 | Lifting points | 11 |
| 5.2 | Design requirements | 12 |
| 5.2.1 | Protection against ejected fluids | 12 |
| 5.2.2 | Roof contact advance | 12 |
| 5.2.3 | Pressure limiting | 12 |
| 5.2.4 | Interruption of the operating pressure | 12 |
| 5.2.5 | Travel speeds | 12 |
| 5.2.6 | Actuating forces | 12 |
| 5.2.7 | Resistance to back pressure | 12 |
| 5.2.8 | Adjustable valves | 12 |
| 5.3 | Requirements of type A valves | 12 |
| 5.3.1 | General | 12 |
| 5.3.2 | Leaktightness | 12 |
| 5.3.3 | Yield pressure | 13 |
| 5.3.4 | Opening pressure | 13 |
| 5.3.5 | Closing pressure | 13 |
| 5.3.6 | Pressure pulses | 13 |
| 5.3.7 | Impact resistance | 13 |
| 5.3.8 | Pressure flow behaviour | 13 |
| 5.3.9 | Operating reliability | 13 |
| 5.3.10 | Temperature effects | 13 |
| 5.3.11 | Resistance to back pressure | 13 |
| 5.4 | Requirements for type B and C valves | 13 |
| 5.4.1 | General | 13 |
| 5.4.2 | Leaktightness | 13 |
| 5.4.3 | Resistance to pressure | 14 |
| 5.4.4 | Switching behaviour | 14 |

| | | |
|---|---|-----------|
| 5.4.5 | Operating reliability | 14 |
| 5.4.6 | Resistance to back pressure | 14 |
| 5.5 | Requirements for type D valves | 14 |
| 5.6 | Materials | 14 |
| 5.6.1 | Metallic materials | 14 |
| 5.6.2 | Light metal | 14 |
| 5.6.3 | Other materials | 14 |
| 5.6.4 | Seals | 14 |
| 6 | Verification of the safety requirements | 15 |
| 6.1 | Type testing | 15 |
| 6.2 | Additional tests | 15 |
| 7 | User Information | 17 |
| 7.1 | General requirements | 17 |
| 7.2 | Technical and application data | 17 |
| 7.2.1 | Introduction | 17 |
| 7.2.2 | General description | 17 |
| 7.2.3 | Performance data | 17 |
| 7.2.4 | Hydraulic data | 17 |
| 7.2.5 | List of additional drawings and documents | 17 |
| 7.3 | Handling, transport and storage | 18 |
| 7.3.1 | Introduction | 18 |
| 7.3.2 | Handling and transport | 18 |
| 7.3.3 | Storage | 18 |
| 7.4 | Installation and commissioning | 18 |
| 7.4.1 | Installation | 18 |
| 7.4.2 | Commissioning | 18 |
| 7.5 | Operation | 18 |
| 7.6 | Maintenance | 19 |
| 7.6.1 | Introduction | 19 |
| 7.6.2 | Technical description | 19 |
| 7.6.3 | Maintenance instructions | 19 |
| 7.6.4 | Fault diagnosis and correction | 19 |
| 7.6.5 | Preventative maintenance schedules | 19 |
| 7.7 | Parts identification lists | 19 |
| 7.8 | Marking | 19 |
| 7.9 | Residual risks | 20 |
| Annex A (normative) Tests for verification of the safety requirements | | 21 |
| A.1 | Load tests | 21 |
| A.1.1 | General | 21 |
| A.1.2 | Lifting points | 21 |
| A.1.3 | Testing of type A valves | 21 |
| A.1.4 | Testing of type B valves | 26 |
| A.1.5 | Testing of type C valves | 29 |
| A.1.6 | Testing of type D valves | 30 |
| Annex B (normative) Deviations from EN 982:1996 | | 31 |
| B.1 | General | 31 |
| B.2 | 5.1.7 (EN 982:1996) | 31 |
| B.3 | 5.3.4.1.3 Contamination control (EN 982:1996) | 32 |
| B.4 | 5.3.4.3.2 Failure (EN 982:1996) | 32 |
| B.5 | 5.3.6 Sequence control (EN 982:1996) | 32 |
| B.6 | 7.3.4.1 Non-electrical control mechanisms (EN 982:1996) | 32 |
| Annex ZA (informative) Relationship between this European Standard and the Essential Requirements of EU Directive 2006/42/EC | | 33 |
| Bibliography | | 34 |