

DIN ISO 3601-4:2010-08 (E)

Fluid power systems - O-rings - Part 4: Anti-extrusion rings (back-up rings) (ISO 3601-4:2008)

| Contents | | Page |
|-------------------------|---|-------------|
| National foreword | | 3 |
| Introduction | | 4 |
| 1 | Scope | 5 |
| 2 | Normative references | 5 |
| 3 | Terms and definitions | 5 |
| 4 | Symbols | 6 |
| 5 | General requirements related to O-ring housings | 6 |
| 6 | Types of anti-extrusion (back-up) rings | 7 |
| 6.1 | Spiral type, T1 | 7 |
| 6.2 | Angle cut type, T2 | 9 |
| 6.3 | Solid type, T3 | 9 |
| 6.4 | Angle cut concave type, T4 | 10 |
| 6.5 | Solid concave type, T5 | 11 |
| 7 | Positioning of anti-extrusion rings in housings | 12 |
| 8 | Anti-extrusion ring designation code and materials | 12 |
| 8.1 | Designation code | 12 |
| 8.2 | Materials | 13 |
| 9 | Dimensions and tolerances | 13 |
| 9.1 | Axial and radial widths of anti-extrusion rings | 13 |
| 9.2 | Outside diameters of anti-extrusion rings for piston sealing applications | 14 |
| 9.3 | Inside diameters of anti-extrusion rings for rod sealing applications | 15 |
| 10 | Identification statement (reference to this part of ISO 3601) | 15 |