

DIN EN ISO 5801:2010-12 (E)

Industrial fans - Performance testing using standardized airways (ISO 5801:2007, including Cor 1:2008)

Contents		Page
Foreword		6
Introduction		
1	Scope	9
2	Normative references	9
3	Terms and definitions	9
4	Symbols and units	24
4.1	Symbols	24
4.2	Subscripts	27
5	General	27
6	Instruments for pressure measurement	28
6.1	Barometers	28
6.2	Manometers	29
6.3	Damping of manometers	29
6.4	Checking of manometers	29
6.5	Position of manometers	30
7	Determination of average pressure in an airway	30
7.1	Methods of measurement	30
7.2	Use of wall tapplings	30
7.3	Construction of tapplings	30
7.4	Position and connections	31
7.5	Checks for compliance	31
7.6	Use of Pitot-static tube	31
8	Measurement of temperature	32
8.1	Thermometers	32
8.2	Thermometer location	32
8.3	Humidity	32
9	Measurement of rotational speed	33
9.1	Fan shaft speed	33
9.2	Acceptable instruments	33
10	Determination of power input	33
10.1	Measurement accuracy	33
10.2	Fan shaft power	33
10.3	Determination of fan shaft power by electrical measurement	33
10.4	Impeller power	34
10.5	Transmission systems	34
11	Measurement of dimensions and determination of areas	34
11.1	Flow-measurement devices	34
11.2	Tolerance on dimensions	34
11.3	Determination of cross-sectional area	35

12	Determination of air density, humid gas constant and viscosity	35
12.1	Density of air in the test enclosure at section x	35
12.2	Determination of vapour pressure	36
12.3	Determination of air viscosity	38
13	Determination of flow rate	39
13.1	General	39
13.2	In-line flowmeters (standard primary devices)	39
13.3	Traverse methods	40
14	Calculation of test results	42
14.1	General	42
14.2	Units	42
14.3	Temperature	42
14.4	Mach number and reference conditions	44
14.5	Fan pressure	48
14.6	Calculation of stagnation pressure at a reference section of the fan from gauge pressure, p_{ex} , measured at a section x of the test duct	51
14.7	Inlet volume flow rate	52
14.8	Fan air power and efficiency	52
15	Rules for conversion of test results	60
15.1	Laws on fan similarity	60
15.2	Conversion rules	62
16	Fan characteristic curves	65
16.1	General	65
16.2	Methods of plotting	66
16.3	Characteristic curves at constant speed	66
16.4	Characteristic curves at inherent speed	66
16.5	Characteristic curves for adjustable-duty fan	67
16.6	Complete fan characteristic curve	68
16.7	Test for a specified duty	69
17	Uncertainty analysis	70
17.1	Principle	70
17.2	Pre-test and post-test analysis	70
17.3	Analysis procedure	70
17.4	Propagation of uncertainties	70
17.5	Reporting uncertainties	71
17.6	Maximum allowable uncertainties measurement	71
17.7	Maximum allowable uncertainty of results	72
18	Selection of test method	73
18.1	Classification	73
18.2	Installation categories	73
18.3	Test report	73
18.4	User installations	74
18.5	Alternative methods	74
18.6	Duct simulation	74
19	Installation of fan and test airways	74
19.1	Inlets and outlets	74
19.2	Airways	74
19.3	Test enclosure	75
19.4	Matching fan and airway	75
19.5	Outlet area	75
20	Carrying out the test	75
20.1	Working fluid	75
20.2	Rotational speed	75

20.3	Steady operation	75
20.4	Ambient conditions	76
20.5	Pressure readings	76
20.6	Tests for a specified duty	76
20.7	Tests for a fan characteristic curve	76
20.8	Operating range	76
21	Determination of flow rate	76
21.1	Multiple nozzle	76
21.2	Conical or bellmouth inlet	76
21.3	Orifice plate	76
21.4	Pilot-static tube traverse (see ISO 3966 and ISO 5221)	77
22	Determination of flow rate using multiple nozzles	77
22.1	Installation	77
22.2	Geometric form	77
22.3	Inlet zone	78
22.4	Multiple-nozzle characteristics	78
22.5	Uncertainty	80
23	Determination of flow rate using a conical or bellmouth inlet	81
23.1	Geometric form	81
23.2	Screen loading	82
23.3	Inlet zone	83
23.4	Conical inlet performance	83
23.5	Bellmouth inlet performance	83
23.6	Uncertainties	85
24	Determination of flow rate using an orifice plate	85
24.1	Installation	85
24.2	Orifice plate	85
24.3	Ducts	89
24.4	Pressure tapings	89
24.5	Calculation of mass flow rate	89
24.6	Reynolds number	90
24.7	In-duct orifice with D and D/2 taps [see Figure 20 a) and ISO 5167-1]	90
24.8	Outlet orifice with wall tapings [see Figure 20 c) and e)]	94
25	Determination of flow rate using a Pitot-static tube traverse	96
25.1	General	96
25.2	Pitot-static tube	96
25.3	Limits of air velocity	101
25.4	Location of measurement points	101
25.5	Determination of flow rate	102
25.6	Flow rate coefficient	102
25.7	Uncertainty of measurement	103
26	Installation and setup categories	103
26.1	Category A: free inlet and free outlet	103
26.2	Category B: free inlet and ducted outlet	103
26.3	Category C: ducted inlet and free outlet	104
26.4	Category D: ducted inlet and ducted outlet	104
26.5	Test installation type	104
27	Flow straighteners	104
27.1	Types of straightener	105
27.2	Rules for use of a straightener	106
28	Common-segment airways for ducted fan installations	107
28.1	Common segments	107
28.2	Common segment at fan outlet	107
28.3	Common segment at fan inlet	109

28.4	Outlet duct simulation	111
28.5	Inlet duct simulation	111
28.6	Loss allowances for standardized airways	112
29	Standardized test chambers	115
29.1	Test chamber	115
29.2	Variable supply and exhaust systems	120
29.3	Standardized inlet test chambers	120
29.4	Standardized outlet test chambers	123
30	Standard methods with test chambers -- Category A installations	126
30.1	Types of fan setup	126
30.2	Inlet-side test chambers	126
30.3	Outlet-side test chambers	139
31	Standard test methods with outlet-side test ducts -- Category B installations	144
31.1	Types of fan setup	144
31.2	Outlet-side test ducts with antiswirl device	145
31.3	Outlet chamber test ducts without antiswirl device	157
32	Standard test methods with inlet-side test ducts or chambers -- Category C installations	164
32.1	Types of fan setup	164
32.2	Inlet-side test ducts	165
32.3	Inlet-side test chambers	178
33	Standard methods with inlet- and outlet-side test ducts -- Category D installations	188
33.1	Types of fan setup	188
33.2	Installation category B with outlet antiswirl device and with an additional inlet duct or inlet-duct simulation	192
33.3	Installation category B without outlet antiswirl device nor common segment, modified with addition of an inlet duct or inlet-duct simulation	198
33.4	Installation category C with common inlet duct, modified with the addition of an outlet common segment with antiswirl device	201
33.5	Installation category C, modified with the addition of an outlet-duct simulation without antiswirl device	205
Annex A (normative) Fan pressure and fan installation category		213
Annex B (normative) Fan-powered roof exhaust ventilators		217
Annex C (informative) Chamber leakage test procedure		219
Annex D (informative) Fan outlet elbow in the case of a non-horizontal discharge axis		225
Annex E (informative) Electrical input power consumed by a fan installation		228
Annex F (informative) Preferred methods of performance testing		235
Bibliography		236