

ISO/TS 10303-5001:2010-11 (E)

Industrial automation systems and integration - Product data representation and exchange - Part 5001: Guidance on the usage of ISO 10303-214 for gear units

| Contents | | Page |
|--------------------|--|-------------|
| Foreword | | viii |
| Introduction | | ix |
| 1 | Scope | 1 |
| 2 | Normative references | 3 |
| 3 | Terms, definitions and abbreviated terms | 3 |
| 3.1 | Terms defined in ISO 10303-1 | 3 |
| 3.2 | Abbreviated terms | 3 |
| 4 | Information requirements | 4 |
| 4.1 | Preliminary elements | 4 |
| 4.2 | Application objects | 4 |
| 4.2.1 | Application_context | 4 |
| 4.2.2 | Application_property | 5 |
| 4.2.3 | Assembly_definition | 5 |
| 4.2.4 | Assembly_relationship | 5 |
| 4.2.5 | Baseplate | 6 |
| 4.2.6 | Basic_material | 6 |
| 4.2.7 | Bearing | 6 |
| 4.2.8 | Bearing_bearing | 7 |
| 4.2.9 | Belt_or_chain | 7 |
| 4.2.10 | Bevel_or_hypoid_gear | 7 |
| 4.2.11 | Bevel_or_hypoid_gear_pair | 7 |
| 4.2.12 | Clutch_or_brake | 7 |
| 4.2.13 | Coordinate_definition | 8 |
| 4.2.14 | Coupling | 8 |
| 4.2.15 | Crossed_helical_gear | 8 |
| 4.2.16 | Crossed_helical_gear_pair | 8 |
| 4.2.17 | Cylindrical_gear | 8 |
| 4.2.18 | Cylindrical_gear_pair | 9 |
| 4.2.19 | Data_environment | 9 |
| 4.2.20 | Deformation_shift_bending | 9 |
| 4.2.21 | Direction_definition | 9 |
| 4.2.22 | Document_assignment | 10 |
| 4.2.23 | Dynamic | 11 |
| 4.2.24 | Efficiency_loss | 11 |
| 4.2.25 | Environment | 11 |
| 4.2.26 | External_geometric_model | 11 |
| 4.2.27 | Fit_of_key_assembly | 11 |
| 4.2.28 | Fitting_key | 12 |
| 4.2.29 | Functional_relationship | 12 |
| 4.2.30 | Gear | 12 |
| 4.2.31 | Gear_pair | 12 |
| 4.2.32 | Gear_unit | 13 |
| 4.2.33 | General_gear_pair | 13 |
| 4.2.34 | General_property | 13 |
| 4.2.35 | Geometric_model | 14 |
| 4.2.36 | Geometry_property | 14 |

| | | |
|--------|--|----|
| 4.2.37 | Hardness | 15 |
| 4.2.38 | Housing | 15 |
| 4.2.39 | Housing_baseplate | 16 |
| 4.2.40 | Housing_bearing | 16 |
| 4.2.41 | Housing_clutch_or_brake | 16 |
| 4.2.42 | Housing_coupling | 16 |
| 4.2.43 | Housing_sealing | 17 |
| 4.2.44 | Interference_fit_assembly | 17 |
| 4.2.45 | Life_time | 17 |
| 4.2.46 | Load_capacity | 17 |
| 4.2.47 | Lubricant | 17 |
| 4.2.48 | Lubricant_definition | 18 |
| 4.2.49 | Lubricant_part | 18 |
| 4.2.50 | Manufacturing | 18 |
| 4.2.51 | Material_definition | 18 |
| 4.2.52 | Material_part | 19 |
| 4.2.53 | Material_property | 19 |
| 4.2.54 | Material_property_association | 19 |
| 4.2.55 | Material_property_value_definition | 19 |
| 4.2.56 | Mesh | 20 |
| 4.2.57 | Numerical_value | 20 |
| 4.2.58 | Parameter_property | 20 |
| 4.2.59 | Part | 21 |
| 4.2.60 | Partial_document_assignment | 21 |
| 4.2.61 | Partial_part_shape_definition | 22 |
| 4.2.62 | Part_definition | 24 |
| 4.2.63 | Part_definition_relationship | 24 |
| 4.2.64 | Part_instance | 25 |
| 4.2.65 | Part_shape_definition | 25 |
| 4.2.66 | Part_version | 26 |
| 4.2.67 | Pinion_shaft | 26 |
| 4.2.68 | Placement_reference_relationship | 26 |
| 4.2.69 | Placement_relationship | 27 |
| 4.2.70 | Plain_bearing | 27 |
| 4.2.71 | Planetary_gear_train | 27 |
| 4.2.72 | Position_orientation_property | 27 |
| 4.2.73 | Position_orientation_property_value | 28 |
| 4.2.74 | Position_orientation_property_value_definition | 28 |
| 4.2.75 | Power_rotation_speed | 29 |
| 4.2.76 | Pressure_stress | 29 |
| 4.2.77 | Property | 29 |
| 4.2.78 | Property_value | 30 |
| 4.2.79 | Property_value_definition | 30 |
| 4.2.80 | Rolling_element_bearing | 31 |
| 4.2.81 | Safety | 31 |
| 4.2.82 | Sealing | 31 |
| 4.2.83 | Service_property | 32 |
| 4.2.84 | Shaft | 32 |
| 4.2.85 | Shaft_bearing | 32 |
| 4.2.86 | Shaft_clutch_or_brake | 32 |
| 4.2.87 | Shaft_collar | 32 |
| 4.2.88 | Shaft_sealing | 33 |
| 4.2.89 | Shaft_shaft | 33 |
| 4.2.90 | Shaft_wheel | 33 |
| 4.2.91 | Shape_description_association | 33 |
| 4.2.92 | Single_part_definition | 34 |
| 4.2.93 | Sliding_wear | 34 |
| 4.2.94 | Specification_property | 34 |
| 4.2.95 | Stiffness_suspension | 34 |
| 4.2.96 | String_value | 34 |
| 4.2.97 | Surface_condition | 35 |
| 4.2.98 | Surface_condition_association | 35 |

| | | |
|---------|---|----|
| 4.2.99 | Surface_texture | 35 |
| 4.2.100 | Surface_texture_parameter | 36 |
| 4.2.101 | Temperature | 37 |
| 4.2.102 | Tool | 37 |
| 4.2.103 | Tool_part_relationship | 37 |
| 4.2.104 | Torque_force | 38 |
| 4.2.105 | Unit | 38 |
| 4.2.106 | User_defined_part | 38 |
| 4.2.107 | User_defined_relationship | 39 |
| 4.2.108 | Value_association | 39 |
| 4.2.109 | Value_limit | 39 |
| 4.2.110 | Value_list | 40 |
| 4.2.111 | Value_range | 40 |
| 4.2.112 | Value_with_unit | 41 |
| 4.2.113 | Wheel | 41 |
| 4.2.114 | Wheel_bearing | 41 |
| 4.2.115 | Wheel_belt_or_chain | 42 |
| 4.2.116 | Wheel_wheel | 42 |
| 4.2.117 | Worm | 42 |
| 4.2.118 | Worm_gear_pair | 42 |
| 4.2.119 | Worm_wheel | 42 |
| 4.3 | Application assertions | 43 |
| 4.3.1 | Assembly_relationship to Assembly_definition | 43 |
| 4.3.2 | Assembly_relationship to Part_instance | 43 |
| 4.3.3 | Coordinate_definition to Value_with_unit | 43 |
| 4.3.4 | Direction_definition to Value_with_unit | 43 |
| 4.3.5 | Document_assignment to Assembly_relationship | 43 |
| 4.3.6 | Document_assignment to Partial_part_shape_definition | 43 |
| 4.3.7 | Document_assignment to Part_definition | 43 |
| 4.3.8 | Document_assignment to Part_definition_relationship | 43 |
| 4.3.9 | Document_assignment to Part_shape_definition | 44 |
| 4.3.10 | Document_assignment to Tool_part_relationship | 44 |
| 4.3.11 | Geometry_property to Partial_Part_shape_definition | 44 |
| 4.3.12 | Geometry_property to Part_shape_definition | 44 |
| 4.3.13 | Hardness to Value_with_unit | 44 |
| 4.3.14 | Material_definition to Part_definition | 44 |
| 4.3.15 | Material_property_association to Material_definition | 44 |
| 4.3.16 | Material_property_association to Material_property_value_definition | 44 |
| 4.3.17 | Material_property_value_definition to Material_property | 45 |
| 4.3.18 | Material_property_value_definition to Data_environment | 45 |
| 4.3.19 | Part_definition to Application_context | 45 |
| 4.3.20 | Part_definition to Part_version | 45 |
| 4.3.21 | Part_definition_relationship to Part_definition | 45 |
| 4.3.22 | Part_instance to Part_definition | 45 |
| 4.3.23 | Partial_part_shape_definition to Part_shape_definition | 45 |
| 4.3.24 | Part_shape_definition to Part_definition | 45 |
| 4.3.25 | Part_shape_definition to Part_instance | 46 |
| 4.3.26 | Part_version to Part | 46 |
| 4.3.27 | Placement_reference_relationship to Position_orientation_property_value_definition | 46 |
| 4.3.28 | Placement_relationship to Position_orientation_property_value_definition | 46 |
| 4.3.29 | Placement_relationship to Property_value_definition | 46 |
| 4.3.30 | Position_orientation_property_value to Coordinate_definition | 46 |
| 4.3.31 | Position_orientation_property_value to Direction_definition | 46 |
| 4.3.32 | Position_orientation_property_value_definition to Position_orientation_property | 46 |
| 4.3.33 | Position_orientation_property_value_definition to Position_orientation_property_value | 46 |
| 4.3.34 | Property to Unit | 47 |
| 4.3.35 | Property_value_definition to Property | 47 |
| 4.3.36 | Property_value_definition to Property_value | 47 |
| 4.3.37 | Shape_description_association to External_geometric_model | 47 |
| 4.3.38 | Shape_description_association to Geometric_model | 47 |
| 4.3.39 | Shape_description_association to Partial_part_shape_definition | 47 |
| 4.3.40 | Shape_description_association to Part_shape_definition | 47 |

| | | |
|--|--|-----|
| 4.3.41 | Surface_condition_association to Part_shape_definition | 47 |
| 4.3.42 | Surface_condition_association to Partial_part_shape_definition | 48 |
| 4.3.43 | Surface_condition_association to Surface_condition | 48 |
| 4.3.44 | Surface_texture_parameter to Surface_texture | 48 |
| 4.3.45 | Surface_texture_parameter to Value_with_unit | 48 |
| 4.3.46 | Tool_part_relationship to Part_definition | 48 |
| 4.3.47 | Value_association to Assembly_relationship | 48 |
| 4.3.48 | Value_association to Partial_part_shape_definition | 48 |
| 4.3.49 | Value_association to Part_definition | 49 |
| 4.3.50 | Value_association to Part_definition_relationship | 49 |
| 4.3.51 | Value_association to Part_shape_definition | 49 |
| 4.3.52 | Value_association to Property_value_definition | 49 |
| 4.3.53 | Value_association to Tool_part_relationship | 49 |
| 4.3.54 | Value_list to Property_value | 49 |
| 5 | Mapping to ISO 10303-214 | 49 |
| 6 | Conformance requirements | 71 |
| Annex A (informative) Product model for gear units | | 72 |
| Annex B (informative) Property tables for gear units | | 84 |
| Annex C (informative) Mapping mechanism | | 148 |
| Annex D (informative) Mapping to relevant explicit ARM constructs of ISO 10303-224 | | 149 |
| Bibliography | | 150 |
| Index | | 152 |
| Figures Figure A.1 -- Product model for gear units EXPRESS-G diagram: 1 of 11 | | 73 |
| Figure A.2 -- Product model for gear units EXPRESS-G diagram: 2 of 11 | | 74 |
| Figure A.3 -- Product model for gear units EXPRESS-G diagram: 3 of 11 | | 75 |
| Figure A.4 -- Product model for gear units EXPRESS-G diagram: 4 of 11 | | 76 |
| Figure A.5 -- Product model for gear units EXPRESS-G diagram: 5 of 11 | | 77 |
| Figure A.6 -- Product model for gear units EXPRESS-G diagram: 6 of 11 | | 78 |
| Figure A.7 -- Product model for gear units EXPRESS-G diagram: 7 of 11 | | 79 |
| Figure A.8 -- Product model for gear units EXPRESS-G diagram: 8 of 11 | | 80 |
| Figure A.9 -- Product model for gear units EXPRESS-G diagram: 9 of 11 | | 81 |
| Figure A.10 -- Product model for gear units EXPRESS-G diagram: 10 of 11 | | 82 |
| Figure A.11 -- Product model for gear units EXPRESS-G diagram: 11 of 11 | | 83 |
| Figure C.1 -- Connection between product model for gear units and ISO 10303-214 | | 148 |
| Tables Table 1 -- Mapping table for ARM level of ISO 10303-214 | | 51 |
| Table B.1 -- Deformation shift bending | | 88 |
| Table B.2 -- Dynamic | | 89 |
| Table B.3 -- Efficiency loss | | 90 |

| | |
|--|------------|
| Table B.4 -- Environment | 92 |
| Table B.5 -- Geometry property | 93 |
| Table B.6 -- Hardness | 102 |
| Table B.7 -- Life time | 103 |
| Table B.8 -- Load capacity - factors | 104 |
| Table B.9 -- Load capacity - strength | 113 |
| Table B.10 -- Manufacturing | 116 |
| Table B.11 -- Mesh | 118 |
| Table B.12 -- Parameter property | 122 |
| Table B.13 -- Power rotation speed | 129 |
| Table B.14 -- Pressure stress | 131 |
| Table B.15 -- Safety | 133 |
| Table B.16 -- Service property | 134 |
| Table B.17 -- Sliding wear | 136 |
| Table B.18 -- Specification property | 137 |
| Table B.19 -- Stiffness suspension | 140 |
| Table B.20 -- Surface texture | 141 |
| Table B.21 -- Temperature | 142 |
| Table B.22 -- Torque force | 145 |
| Table D.1 -- Mapping table for ARM level of ISO 10303-224 | 149 |