

DIN EN 500-4:2011-06 (E)

Mobile road construction machinery - Safety - Part 4: Specific requirements for compaction machines

| Contents | | Page |
|--|--|-------------|
| Foreword | | 6 |
| Introduction | | 8 |
| 1 | Scope | 8 |
| 2 | Normative references | 8 |
| 3 | Terms and definitions | 9 |
| 4 | List of significant hazards | 11 |
| 5 | Safety requirements and/or protective measures | 11 |
| 5.1 | Lighting, signalling and marking lights and reflex-reflector devices | 11 |
| 5.2 | Operation and handling | 11 |
| 5.2.1 | Retrieval transportation and towing | 11 |
| 5.2.2 | Pedestrian-controlled rollers | 11 |
| 5.3 | Operator's station | 13 |
| 5.4 | Operator's seat | 13 |
| 5.5 | Controls and indicators | 13 |
| 5.5.1 | General | 13 |
| 5.5.2 | Travel control of pedestrian-controlled machines with handle bar | 13 |
| 5.5.3 | Controls for towed machines | 13 |
| 5.5.4 | Remote control of pedestrian-controlled rollers | 13 |
| 5.6 | Starting | 14 |
| 5.7 | Stopping | 14 |
| 5.7.1 | General | 14 |
| 5.7.2 | Stopping device | 14 |
| 5.7.3 | Braking systems | 14 |
| 5.8 | Access system to operator's station and to maintenance points | 15 |
| 5.9 | Roll-over protective structure (ROPS) | 15 |
| 5.10 | Noise and vibration | 16 |
| 5.10.1 | Noise measurement of vibratory plates and vibratory rammers | 16 |
| 5.10.2 | Noise measurement of rollers | 16 |
| 5.10.3 | Vibration measurement of hand-guided machines | 16 |
| 6 | Verification of safety requirements and/or protective measures | 17 |
| 7 | Information for the user | 17 |
| 7.1 | Warning signals and devices | 17 |
| 7.2 | Instruction handbook | 17 |
| 7.3 | Marking | 18 |
| Annex A (normative) Remote infrared controls for rollers with attending operator | | 19 |
| A.1 | General | 19 |
| A.2 | Scope | 19 |
| A.3 | Terms and definitions | 19 |
| A.4 | Safety requirements and measures | 19 |
| A.5 | Components and equipment | 21 |

| | |
|--|-----------|
| Annex B (normative) Noise-test-code for vibratory plates and vibratory rammers | 23 |
| B.1 Scope | 23 |
| B.2 Determination of the A-weighted sound power level | 23 |
| B.2.1 General | 23 |
| B.2.2 Measurement surface | 24 |
| B.2.3 Test procedure | 28 |
| B.2.4 Repetition of the test and calculation of the sound power level | 28 |
| B.3 Determination of the A-weighted emission sound pressure level at the operator's position | 29 |
| B.3.1 General | 29 |
| B.3.2 Operator's position | 29 |
| B.3.3 Test procedure | 29 |
| B.3.4 Repetition of the test and calculation of the emission sound pressure level | 29 |
| B.3.5 Determination of emission sound pressure spectra | 29 |
| B.3.6 Sound pressure level as a function of time | 29 |
| B.4 Installation and mounting conditions | 30 |
| B.4.1 General | 30 |
| B.4.2 Design of the test surface | 30 |
| B.4.3 Design of the test site | 31 |
| B.5 Operating conditions | 33 |
| B.6 Uncertainty | 33 |
| B.7 Information to be recorded | 33 |
| B.8 Information to be reported | 34 |
| B.9 Declaration and verification of noise emission values | 35 |
| | |
| Annex C (normative) Measurement of the hand-arm vibration of hand-guided vibratory ground compaction machines | 36 |
| C.1 General | 36 |
| C.2 Terminology | 36 |
| C.3 Quantities to be measured | 36 |
| C.3.1 R.m.s. value of the weighted acceleration | 36 |
| C.3.2 Frequency analysis | 36 |
| C.3.3 Time records | 37 |
| C.3.4 Other quantities to be measured | 37 |
| C.4 Measuring equipment | 37 |
| C.4.1 Requirements for the acceleration transducers | 37 |
| C.4.2 Fastening of the acceleration transducers | 37 |
| C.4.3 Frequency weighting filter | 37 |
| C.4.4 R.m.s. detector | 37 |
| C.4.5 Calibration | 37 |
| C.5 Measurement direction and measurement location | 38 |
| C.5.1 Measurement direction | 38 |
| C.5.2 Measurement location | 40 |
| C.6 Specification of working procedure | 40 |
| C.6.1 Operator | 40 |
| C.6.2 Other quantities to be determined (forces) | 40 |
| C.6.3 Operating conditions | 40 |
| C.6.4 Requirements for the test site | 40 |
| C.6.5 Measurement procedure | 41 |
| C.7 Test report | 41 |
| C.7.1 Reference | 41 |
| C.7.2 Description of the object to be measured | 41 |
| C.7.3 List of measuring equipment | 41 |
| C.7.4 Fastening of the acceleration transducers | 41 |
| C.7.5 Operating conditions | 41 |
| C.7.6 Further specifications | 41 |
| C.7.7 Results | 42 |
| C.8 Report of results | 42 |
| C.9 Measurement uncertainty | 42 |

| | |
|---|-----------|
| Annex D (normative) Noise test code for vibratory rollers | 43 |
| D.1 Scope | 43 |
| D.2 Determination of the A-weighted sound power level | 43 |
| D.2.1 General | 43 |
| D.2.2 Measurement surface | 43 |
| D.2.3 Positioning of the machine | 45 |
| D.2.4 Repetition of the test | 49 |
| D.3 Determination of the A-weighted emission sound pressure level at the operators positions for vibratory rollers | 49 |
| D.3.1 General | 49 |
| D.3.2 Operator's positions | 49 |
| D.3.3 Enclosed operator's positions | 49 |
| D.3.4 Quantities to be determined | 49 |
| D.3.5 Microphone position(s) | 49 |
| D.3.6 Test procedure | 49 |
| D.3.7 Repetition of the test | 50 |
| D.4 Test conditions | 50 |
| D.4.1 Installation and mounting conditions | 50 |
| D.4.2 Operating conditions | 50 |
| D.5 Uncertainty | 50 |
| D.6 Information to be recorded | 51 |
| D.7 Information to be reported | 51 |
| D.8 Declaration and verification of noise emission values | 52 |
| Annex E (normative) Noise test code for non-vibrating rollers | 53 |
| E.1 Scope | 53 |
| E.2 Determination of the A-weighted sound power level | 53 |
| E.2.1 General | 53 |
| E.2.2 Measurement surface | 53 |
| E.2.3 Positioning of the machine | 55 |
| E.2.4 Repetition of the test | 56 |
| E.3 Determination of the A-weighted emission sound pressure level at operator's positions for non-vibrating rollers | 56 |
| E.3.1 General | 56 |
| E.3.2 Operators positions | 56 |
| E.3.3 Enclosed operator's positions | 56 |
| E.3.4 Quantities to be determined | 56 |
| E.3.5 Microphone position(s) | 56 |
| E.3.6 Test procedure | 56 |
| E.3.7 Repetition of the test | 57 |
| E.4 Test conditions | 57 |
| E.4.1 Installation and mounting conditions | 57 |
| E.4.2 Operating conditions | 57 |
| E.5 Uncertainty | 57 |
| E.6 Information to be recorded | 58 |
| E.7 Information to be reported | 58 |
| E.8 Declaration and verification of noise emission values | 59 |
| Annex ZA (informative) Relationship between this European Standard and the Essential Requirements of EU Directive 2006/42/EC | 60 |
| Bibliography | 61 |
| Figures Figure 1 -- Vertical swinging of single-drum walk-behind rollers | 12 |
| Figure 2 -- Position of the stopping device at pedestrian-controlled rollers | 13 |
| Figure 3 -- Minimum clearance of lower limbs at access to the operator's station on machines with articulated steering | 15 |

| | |
|--|----|
| Figure 4 -- Deflection-limiting volume, front view, side view | 16 |
| Figure 5 -- Warning decal | 17 |
| Figure B.1 -- Arrangement of test positions for hand-guided vibratory plates and hand-guided vibratory rammers | 25 |
| Figure B.2 -- Arrangement of test positions for remote controlled vibratory plates | 27 |
| Figure B.3 -- Grading-size diagram of the material to be compacted (gravel) | 31 |
| Figure B.4 -- Test site and arrangement with test track | 32 |
| Figure C.1 -- Directions of measurement and examples for attachment of the acceleration transducer | 39 |
| Figure C.2 -- Arrangement of the coupling device on the drawbar | 40 |
| Figure D.1 -- Basic length L | 44 |
| Figure D.2 -- Arrangement of test positions for ride-on vibratory rollers | 45 |
| Figure D.3 -- Arrangement of test positions for hand-guided vibratory rollers | 46 |
| Figure D.4 -- Arrangement of test positions for remote controlled vibratory rollers | 47 |
| Figure D.5 -- Arrangement of test positions for towed vibratory rollers | 48 |
| Figure E.1 -- Basic length L | 54 |
| Figure E.2 -- Microphone positions | 55 |
| Tables Table B.1 -- Coordinates of microphones | 28 |
| Table B.2 -- Operating conditions | 33 |
| Table B.3 -- Uncertainties applicable to gravel course | 33 |
| Table D.2 -- Uncertainties applicable to cushion mounted machines | 50 |
| Table E.1 -- Coordinates of microphone positions | 54 |
| Table E.2 -- Uncertainties | 57 |