

# ISO/TR 22849:2011-04 (E)

## Design recommendations for bevel gears

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Symbols, descriptions and units .....</b>	<b>1</b>
<b>3</b>	<b>Application .....</b>	<b>3</b>
<b>3.1</b>	<b>Geometry .....</b>	<b>3</b>
<b>3.2</b>	<b>Rating .....</b>	<b>3</b>
<b>3.3</b>	<b>Materials .....</b>	<b>4</b>
<b>3.4</b>	<b>Gear tolerances .....</b>	<b>4</b>
<b>3.5</b>	<b>Gear noise .....</b>	<b>4</b>
<b>4</b>	<b>Manufacturing consideration .....</b>	<b>8</b>
<b>4.1</b>	<b>Outline of production methods and their features -- Face milling and face hobbing .....</b>	<b>8</b>
<b>4.2</b>	<b>Blank design and tolerances .....</b>	<b>9</b>
<b>4.3</b>	<b>Assembly .....</b>	<b>18</b>
<b>4.4</b>	<b>Tooth contact pattern .....</b>	<b>23</b>
<b>5</b>	<b>Strength considerations .....</b>	<b>25</b>
<b>5.1</b>	<b>Effect of hypoid offset .....</b>	<b>25</b>
<b>5.2</b>	<b>Effect of cutter radius .....</b>	<b>25</b>
<b>5.3</b>	<b>Bevel gear mountings .....</b>	<b>27</b>
<b>5.4</b>	<b>Direction of forces .....</b>	<b>29</b>
<b>6</b>	<b>Efficiency considerations .....</b>	<b>29</b>
<b>6.1</b>	<b>Hypoid and bevel gear mesh efficiency .....</b>	<b>29</b>
<b>6.2</b>	<b>Lubrication .....</b>	<b>33</b>
Bibliography .....		37