

# DIN 743-1:2012-12 (E)

## Calculation of load capacity of shafts and axles - Part 1: General

---

<b>Contents</b>		<b>Page</b>
Foreword.....		3
Introduction .....		5
1 Scope .....		6
2 Normative references .....		7
3 Symbols, designations and units.....		7
4 Proof of avoidance of fatigue failure .....		9
4.1 Factor of safety .....		9
4.2 Working stresses .....		10
4.3 Fatigue strength value .....		10
5 Proof of avoidance of permanent deformation, incipient cracking or overload breakage under maximum load.....		14
5.1 Safety factor .....		14
5.1.1 Proof of avoidance of permanent deformation.....		15
5.1.2 Proof of avoidance of incipient cracking (and/or overload breakage) in hard surfaces .....		16
5.2 Component yield point.....		16
5.3 Component's incipient crack limit .....		17
5.4 Working stresses (maximum stresses).....		18
<b>Annex A (informative) Explanations of the variation of load and/or stress, cross-sectional areas and the reading of <math>\sigma_{ADK}</math> from the Smith diagram .....</b>		<b>19</b>
<b>Annex B (normative) Schema of the safety factor calculation .....</b>		<b>22</b>
B.1 General schema .....		22
B.2 Total influence factor .....		24
Bibliography .....		25
 <b>Figures</b>		
Figure A.1 — Variation of applied load with time ( $F_{zd}, M_b, M_t$ ) and stress ( $\sigma_{zd}, \sigma_b, \tau_t$ ).....		19
Figure A.2 — Origination of amplitude of bending moment $M_b$ as a result of shaft rotation (rotational bending); force $F$ with constant direction, shaft rotating ( $\omega = 2 \cdot \pi \cdot n > 0$ ) .....		19
Figure A.3 — Cross section parameters .....		19
Figure A.4 — Load cases, represented in the fatigue strength diagram (Smith diagram).....		20
Figure A.5 — Fatigue strength diagram with extension of the compression zone (component pressure yield point $\sigma_{dFK}$ ) .....		21
Figure B.1 — Calculation procedure for safety factors .....		23
Figure B.2 — Calculation procedure for total influence factor $K_{\sigma, \tau}$ .....		24

## Tables

<b>Table 1 — Determination of working stresses .....</b>	<b>10</b>
<b>Table 2 — Increase factor for yield point <math>\gamma_F</math> at circumferential notch (<math>\alpha_\sigma</math> and/or <math>\beta_\sigma</math> according to DIN 743-2) and materials without hard surface.....</b>	<b>17</b>
<b>Table 3 — Static support factor <math>K_{2F}</math> for materials without hard surface .....</b>	<b>17</b>
<b>Table 4 — Determination of maximum stresses (maximum nominal stresses) .....</b>	<b>18</b>
<b>Table A1 — <math>\sigma_{ADK}</math> in the marked compression zone for load case 1 with <math>\sigma_{mv} &lt; \sigma_{mv \text{ grenz F1}}</math> and/or for load case 2 with <math>\sigma_{mv}/\sigma_a &lt; (\sigma_{mv}/\sigma_a)_{\text{grenz F2}}</math> (in the compression zone <math>\sigma_{mv} &lt; 0</math> or <math>\sigma_{mv}/\sigma_a &lt; 0</math> applies) .....</b>	<b>21</b>