

DIN 743-1:2012-12 (E)

Calculation of load capacity of shafts and axles - Part 1: General

| Contents | | Page |
|--|--|-------------|
| Foreword..... | | 3 |
| Introduction | | 5 |
| 1 Scope | | 6 |
| 2 Normative references | | 7 |
| 3 Symbols, designations and units..... | | 7 |
| 4 Proof of avoidance of fatigue failure | | 9 |
| 4.1 Factor of safety | | 9 |
| 4.2 Working stresses | | 10 |
| 4.3 Fatigue strength value | | 10 |
| 5 Proof of avoidance of permanent deformation, incipient cracking or overload breakage under maximum load..... | | 14 |
| 5.1 Safety factor | | 14 |
| 5.1.1 Proof of avoidance of permanent deformation..... | | 15 |
| 5.1.2 Proof of avoidance of incipient cracking (and/or overload breakage) in hard surfaces | | 16 |
| 5.2 Component yield point..... | | 16 |
| 5.3 Component's incipient crack limit | | 17 |
| 5.4 Working stresses (maximum stresses)..... | | 18 |
| Annex A (informative) Explanations of the variation of load and/or stress, cross-sectional areas and the reading of σ_{ADK} from the Smith diagram | | 19 |
| Annex B (normative) Schema of the safety factor calculation | | 22 |
| B.1 General schema | | 22 |
| B.2 Total influence factor | | 24 |
| Bibliography | | 25 |
| Figures | | |
| Figure A.1 — Variation of applied load with time (F_{zd}, M_b, M_t) and stress ($\sigma_{zd}, \sigma_b, \tau_t$)..... | | 19 |
| Figure A.2 — Origination of amplitude of bending moment M_b as a result of shaft rotation (rotational bending); force F with constant direction, shaft rotating ($\omega = 2 \cdot \pi \cdot n > 0$) | | 19 |
| Figure A.3 — Cross section parameters | | 19 |
| Figure A.4 — Load cases, represented in the fatigue strength diagram (Smith diagram)..... | | 20 |
| Figure A.5 — Fatigue strength diagram with extension of the compression zone (component pressure yield point σ_{dFK}) | | 21 |
| Figure B.1 — Calculation procedure for safety factors | | 23 |
| Figure B.2 — Calculation procedure for total influence factor $K_{\sigma, \tau}$ | | 24 |

Tables

| | |
|--|-----------|
| Table 1 — Determination of working stresses | 10 |
| Table 2 — Increase factor for yield point γ_F at circumferential notch (α_σ and/or β_σ according to DIN 743-2) and materials without hard surface..... | 17 |
| Table 3 — Static support factor K_{2F} for materials without hard surface | 17 |
| Table 4 — Determination of maximum stresses (maximum nominal stresses) | 18 |
| Table A1 — σ_{ADK} in the marked compression zone for load case 1 with $\sigma_{mv} < \sigma_{mv\ grenz\ F1}$ and/or for load case 2 with $\sigma_{mv}/\sigma_a < (\sigma_{mv}/\sigma_a)_{grenz\ F2}$ (in the compression zone $\sigma_{mv} < 0$ or $\sigma_{mv}/\sigma_a < 0$ applies) | 21 |