

DIN 743-2:2012-12 (E)

Calculation of load capacity of shafts and axles - Part 2: Theoretical stress concentration factors and fatigue notch factors

Contents

| | Page |
|-------|--|
| 1 | Scope5 |
| 2 | Normative references5 |
| 3 | Symbols, designations and units.....5 |
| 4 | Fatigue notch factor6 |
| 4.1 | Definition of fatigue notch factor6 |
| 4.2 | Experimentally determined fatigue notch factors6 |
| 4.2.1 | Parallel keyway and interference fit.....6 |
| 4.2.2 | Fatigue notch factors for splined shafts, serrated shafts and involute spline shafts.....8 |
| 4.2.3 | Fatigue notch factors for round bars with V-notch..... 10 |
| 4.2.4 | Fatigue notch factors for circumferential rectangular notch 11 |
| 4.3 | Fatigue notch factors for notches with known stress concentration factor 12 |
| 4.3.1 | Shoulder, U-notch, shoulder with undercut, transverse hole 12 |
| 4.3.2 | Notch cases not yet dealt with 14 |
| 5 | Stress concentration factors 14 |
| 5.1 | Definition of stress concentration factor 14 |
| 5.2 | Stress concentration factors for different notch shapes 15 |
| 5.2.1 | Shoulder and U-notch 15 |
| 5.2.2 | Shoulder with undercut..... 22 |
| 5.2.3 | Transverse hole 23 |
| 6 | Size influence factors 24 |
| 6.1 | General information..... 24 |
| 6.2 | Technological size influence factor $K_1(d_{\text{eff}})$ 24 |
| 6.3 | Geometrical size influence factor $K_2(d)$ 26 |
| 6.4 | Geometrical size influence factor $K_3(d)$ 27 |
| 7 | Influence factor for surface roughness $K_{F\sigma,\tau}$ 28 |
| 8 | Influence factor for surface conditioning K_V 30 |
| | Bibliography 34 |

Figures

| |
|--|
| Figure 1— Fatigue notch factors for splined shafts, serrated shafts and involute spline shafts 8 |
| Figure 2 — Fatigue notch factors for round bars with circumferential V-notch [2]..... 10 |
| Figure 3 — Circumferential rectangular notch for circlips according to DIN 471 and structural radius ρ^* according to Neuber [9] 11 |
| Figure 4 — Sensitivity factor n 13 |
| Figure 5 — Stress concentration factors for notched round bars in tension 16 |
| Figure 6 — Stress concentration factors for notched round bars in bending 17 |
| Figure 7 — Stress concentration factors for notched round bars in torsion 18 |
| Figure 8 — Stress concentration factors for shouldered round bars in tension 19 |
| Figure 9 — Stress concentration factors for shouldered round bars in bending 20 |
| Figure 10 — Stress concentration factors for shouldered round bars in torsion 21 |

| | |
|--|-----------|
| Figure 11 — Shoulder with undercut..... | 22 |
| Figure 12 — Stress concentration factors for round bars with transverse hole in tension/ compression, bending or torsion (tension/compression [2], bending and torsion [1]) | 23 |
| Figure 13 — Technological size influence factor $K_1(d_{\text{eff}})$ | 25 |
| Figure 14 — Geometrical size influence factor $K_2(d)$ | 26 |
| Figure 15 — Geometrical size influence factor $K_3(d)$ | 27 |
| Figure 16 — Influence factor for surface roughness K_{FO}..... | 29 |
| Figure 17 — Influence factor for surface conditioning, K_V, in chemico-thermal processes | 31 |
| Figure 18 — Influence factor for surface conditioning, K_V, in mechanical processes | 32 |
| Figure 19 — Influence factor for surface conditioning, K_V, in thermal processes | 32 |
| Tables | |
| Table 1 — Fatigue notch factors $\beta_{\sigma,\tau}(d_{BK})$ for shaft-hub connections | 7 |
| Table 2 — Relative stress gradient G'..... | 14 |
| Table 3 — Stress concentration factor constants A, B, C and exponent z..... | 15 |
| Table 4 — Influence factor for surface conditioning, K_V, as a function of the technological process; guidance values | 33 |