

DIN 743-2:2012-12 (E)

Calculation of load capacity of shafts and axles - Part 2: Theoretical stress concentration factors and fatigue notch factors

Contents		Page
1	Scope	5
2	Normative references	5
3	Symbols, designations and units.....	5
4	Fatigue notch factor	6
4.1	Definition of fatigue notch factor	6
4.2	Experimentally determined fatigue notch factors	6
4.2.1	Parallel keyway and interference fit.....	6
4.2.2	Fatigue notch factors for splined shafts, serrated shafts and involute spline shafts.....	8
4.2.3	Fatigue notch factors for round bars with V-notch.....	10
4.2.4	Fatigue notch factors for circumferential rectangular notch	11
4.3	Fatigue notch factors for notches with known stress concentration factor	12
4.3.1	Shoulder, U-notch, shoulder with undercut, transverse hole	12
4.3.2	Notch cases not yet dealt with	14
5	Stress concentration factors	14
5.1	Definition of stress concentration factor	14
5.2	Stress concentration factors for different notch shapes	15
5.2.1	Shoulder and U-notch	15
5.2.2	Shoulder with undercut.....	22
5.2.3	Transverse hole	23
6	Size influence factors	24
6.1	General information.....	24
6.2	Technological size influence factor $K_1(d_{\text{eff}})$	24
6.3	Geometrical size influence factor $K_2(d)$	26
6.4	Geometrical size influence factor $K_3(d)$	27
7	Influence factor for surface roughness $K_{F_{\sigma,t}}$	28
8	Influence factor for surface conditioning K_V	30
	Bibliography	34

Figures

Figure 1— Fatigue notch factors for splined shafts, serrated shafts and involute spline shafts	8
Figure 2 — Fatigue notch factors for round bars with circumferential V-notch [2].....	10
Figure 3 — Circumferential rectangular notch for circlips according to DIN 471 and structural radius ρ^* according to Neuber [9]	11
Figure 4 — Sensitivity factor n	13
Figure 5 — Stress concentration factors for notched round bars in tension	16
Figure 6 — Stress concentration factors for notched round bars in bending	17
Figure 7 — Stress concentration factors for notched round bars in torsion	18
Figure 8 — Stress concentration factors for shouldered round bars in tension.....	19
Figure 9 — Stress concentration factors for shouldered round bars in bending.....	20
Figure 10 — Stress concentration factors for shouldered round bars in torsion	21

Figure 11 — Shoulder with undercut.....	22
Figure 12 — Stress concentration factors for round bars with transverse hole in tension/compression, bending or torsion (tension/compression [2], bending and torsion [1])	23
Figure 13 — Technological size influence factor $K_1(d_{\text{eff}})$	25
Figure 14 — Geometrical size influence factor $K_2(d)$	26
Figure 15 — Geometrical size influence factor $K_3(d)$	27
Figure 16 — Influence factor for surface roughness $K_{F\sigma}$.....	29
Figure 17 — Influence factor for surface conditioning, K_V, in chemico-thermal processes	31
Figure 18 — Influence factor for surface conditioning, K_V, in mechanical processes	32
Figure 19 — Influence factor for surface conditioning, K_V, in thermal processes	32

Tables

Table 1 — Fatigue notch factors $\beta_{\sigma,\tau}(d_{BK})$ for shaft-hub connections	7
Table 2 — Relative stress gradient G'.....	14
Table 3 — Stress concentration factor constants A, B, C and exponent z.....	15
Table 4 — Influence factor for surface conditioning, K_V, as a function of the technological process; guidance values	33