

# ISO 27893:2011-08 (E)

## Vacuum technology - Vacuum gauges - Evaluation of the uncertainties of results of calibrations by direct comparison with a reference gauge

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>2</b>
<b>4</b>	<b>Symbols and abbreviated terms .....</b>	<b>3</b>
<b>5</b>	<b>Basic concept and model .....</b>	<b>3</b>
<b>5.1</b>	<b>General .....</b>	<b>3</b>
<b>5.2</b>	<b>Sum model .....</b>	<b>4</b>
<b>5.3</b>	<b>Quotient model .....</b>	<b>4</b>
<b>5.4</b>	<b>Combination of the two models .....</b>	<b>5</b>
<b>6</b>	<b>Calculation of uncertainty in the sum model .....</b>	<b>5</b>
<b>6.1</b>	<b>Total uncertainty -- Sum model .....</b>	<b>5</b>
<b>6.2</b>	<b>Uncertainty contributions due to reference standard .....</b>	<b>6</b>
<b>6.3</b>	<b>Uncertainty contributions due to unit under calibration .....</b>	<b>7</b>
<b>6.4</b>	<b>Uncertainty contributions due to calibration method or calibration conditions .....</b>	<b>8</b>
<b>6.5</b>	<b>Coverage factor .....</b>	<b>8</b>
<b>7</b>	<b>Calculation of uncertainty in the quotient model .....</b>	<b>9</b>
<b>7.1</b>	<b>Total uncertainty -- Quotient model .....</b>	<b>9</b>
<b>7.2</b>	<b>Uncertainty contributions due to reference standard .....</b>	<b>9</b>
<b>7.3</b>	<b>Uncertainty contributions due to the unit under calibration .....</b>	<b>10</b>
<b>7.4</b>	<b>Uncertainty contributions due to calibration method or calibration conditions .....</b>	<b>11</b>
<b>7.5</b>	<b>Coverage factor .....</b>	<b>12</b>
<b>8</b>	<b>Combination of the sum and quotient model for error of reading .....</b>	<b>13</b>
<b>9</b>	<b>Reporting uncertainties .....</b>	<b>13</b>
<b>9.1</b>	<b>Uncertainty budget .....</b>	<b>13</b>
<b>9.2</b>	<b>Calibration certificate .....</b>	<b>14</b>
Bibliography .....		15