

ISO/TR 15640:2011-12 (E)

Hydraulic fluid power contamination control - General principles and guidelines for selection and application of hydraulic filters

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Types and sources of contamination	1
4.1	General	1
4.2	Solid contaminants	2
4.3	Liquid contaminants	3
4.4	Gaseous contaminants	3
5	Effects of particulate contamination and the benefits of its removal	3
5.1	General	3
5.2	Failures caused by particulate contamination	4
5.3	Benefits of filtration to reduce solid particulate contamination	4
6	Evaluation of cleanliness	4
6.1	General	4
6.2	Particle size range of interest	5
6.3	Methods of measuring and monitoring solid particulate contaminants	5
7	Coding systems for expressing level of solid particulate contamination	6
7.1	General	6
7.2	ISO 4406 coding system	6
7.3	NAS 1638, SAE AS4059 and ISO 11218 coding systems	7
8	Setting required cleanliness levels (RCLs) for a hydraulic system	7
9	Cleanliness management concepts	9
9.1	System design considerations	9
9.2	Monitoring system cleanliness	9
9.3	System maintenance for cleanliness management	10
10	Filters	11
10.1	Mechanisms of filtration	11
10.2	General filter concepts	12
10.3	Types of filters and filter elements	14
10.4	Filter accessories	15
11	Filter evaluation	16
11.1	General	16
11.2	Laboratory filter test methods	16
12	Filter selection process	18
12.1	General	18
12.2	System definition and setting of the RCL	18

12.3	Selecting the minimum recommended filter rating	19
12.4	Filter location	20
12.5	Filter sizing	23
12.6	Assessment of candidate filters	24
12.7	Verification of correct filter selection	24
13	Summary	25
Annex A (informative) Types of filters and separators		26
Bibliography		28