

DIN EN 16297-1:2013-04 (E)

Pumps - Rotodynamic pumps - Glandless circulators - Part 1: General requirements and procedures for testing and calculation of energy efficiency index (EEI)

Contents		Page
Foreword		3
Introduction		4
1	Scope	5
2	Normative references	5
3	Terms and definitions	5
4	Symbols and units	9
5	Performance requirements and safety requirements	9
5.1	Hydraulic characteristics	9
5.1.1	General	9
5.1.2	Q100% and H100%	10
5.2	Rated and minimum power input	10
5.3	Starting characteristics	10
5.4	Resistance to internal pressure	10
5.5	Resistance to thermal cycling	10
5.6	Venting and deblocking	10
5.7	Fluid and structure borne noise emission	10
6	General test methods	10
6.1	General	10
6.2	Testing of the hydraulic characteristic	11
6.2.1	Rated hydraulic output power, $P_{hyd,r}$	11
6.2.2	Reference power, P_{ref}	12
6.2.3	Tolerance on H100% at maximum hydraulic power	12
6.2.4	Reference control curve	13
6.2.5	Load profile for calculation of average compensated power input, PL_{avg}	13
6.2.6	Part load operating points	13
6.2.7	Calculation of compensated power input, PL	16
6.2.8	Calculation of average compensated power input, PL_{avg}	16
6.2.9	Calculation of energy efficiency index (EEI), EEI	16
6.2.10	Test conditions	17
6.2.11	Testing of hydraulic performance	18
6.3	Measurement of rated power input	18
6.4	Starting conditions	18
6.5	Testing of resistance to internal pressure	19
6.6	Testing of resistance to thermal cycling	19
6.6.1	Circulator supply voltage	19
6.6.2	Intermittent operation	19
7	Information for use	20
7.1	General	20
7.2	Instruction handbook	20
7.3	Marking	20
Annex ZA (informative)	Relationship between this European Standard and the requirements of Commission Regulation (EC) No 641/2009	21
Bibliography		22