

# ISO 6162-1:2012-12 (E)

Hydraulic fluid power - Flange connections with split or one-piece flange clamps and metric or inch screws - Part 1: Flange connectors, ports and mounting surfaces for use at pressures of 3,5 MPa (35 bar) to 35 MPa (350 bar), DN 13 to DN 127

---

| <b>Contents</b>    |  | <b>Page</b> |
|--------------------|--|-------------|
| Foreword .....     |  | iv          |
| Introduction ..... |  | v           |
| <b>1</b>           | <b>Scope .....</b>   | <b>1</b>    |
| <b>2</b>           | <b>Normative references .....</b>  | <b>1</b>    |
| <b>3</b>           | <b>Terms and definitions .....</b>   | <b>2</b>    |
| <b>4</b>           | <b>Material .....</b>  | <b>2</b>    |
| <b>5</b>           | <b>Selection .....</b>   | <b>3</b>    |
| <b>6</b>           | <b>Dimensions and tolerances .....</b>   | <b>4</b>    |
| <b>7</b>           | <b>Corrosion protection .....</b>  | <b>4</b>    |
| <b>8</b>           | <b>Pressure/temperature requirements .....</b>   | <b>5</b>    |
| <b>9</b>           | <b>Marking .....</b>   | <b>5</b>    |
| <b>10</b>          | <b>Designation of flange connections and their parts .....</b>   | <b>5</b>    |
|                    | <b>Annex A (informative) Recommended assembly procedures and screw torque levels for flange connections conforming to ISO 6162-1 .....</b> | <b>18</b>   |
|                    | <b>Annex B (informative) O-ring designation codes and dimensions .....</b>   | <b>20</b>   |
|                    | <b>Bibliography .....</b>  | <b>21</b>   |