

# ISO 6162-1:2012-12 (E)

Hydraulic fluid power - Flange connections with split or one-piece flange clamps and metric or inch screws - Part 1: Flange connectors, ports and mounting surfaces for use at pressures of 3,5 MPa (35 bar) to 35 MPa (350 bar), DN 13 to DN 127

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
Introduction .....		v
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>2</b>
<b>4</b>	<b>Material .....</b>	<b>2</b>
<b>5</b>	<b>Selection .....</b>	<b>3</b>
<b>6</b>	<b>Dimensions and tolerances .....</b>	<b>4</b>
<b>7</b>	<b>Corrosion protection .....</b>	<b>4</b>
<b>8</b>	<b>Pressure/temperature requirements .....</b>	<b>5</b>
<b>9</b>	<b>Marking .....</b>	<b>5</b>
<b>10</b>	<b>Designation of flange connections and their parts .....</b>	<b>5</b>
	<b>Annex A (informative) Recommended assembly procedures and screw torque levels for flange connections conforming to ISO 6162-1 .....</b>	<b>18</b>
	<b>Annex B (informative) O-ring designation codes and dimensions .....</b>	<b>20</b>
	<b>Bibliography .....</b>	<b>21</b>