

# ISO 6162-2:2012-12 (E)

Hydraulic fluid power - Flange connections with split or one-piece flange clamps and metric or inch screws - Part 2: Flange connectors, ports and mounting surfaces for use at a pressure of 42 MPa (420 bar), DN 13 to DN 76

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
Introduction .....		v
1	<b>Scope .....</b>	<b>1</b>
2	<b>Normative references .....</b>	<b>1</b>
3	<b>Terms and definitions .....</b>	<b>2</b>
4	<b>Material .....</b>	<b>2</b>
5	<b>Selection .....</b>	<b>3</b>
6	<b>Dimensions and tolerances .....</b>	<b>3</b>
7	<b>Corrosion protection .....</b>	<b>4</b>
8	<b>Pressure/temperature requirements .....</b>	<b>5</b>
9	<b>Marking .....</b>	<b>5</b>
10	<b>Designation of flange connections and their parts .....</b>	<b>5</b>
	<b>Annex A (informative) Recommended assembly procedures and screw torque levels for flange connections conforming to ISO 6162-2 .....</b>	<b>18</b>
	<b>Annex B (informative) O-ring designation codes and dimensions .....</b>	<b>20</b>
	<b>Bibliography .....</b>	<b>21</b>