

ISO/TR 10686:2013-07 (E)

Hydraulic fluid power - Method to relate the cleanliness of a hydraulic system to the cleanliness of the components and hydraulic fluid that make up the system

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Symbols and units	2
5	Basic considerations	3
5.1	Particulate contamination	3
5.2	System knowledge requirements	5
6	Prediction from component cleanliness to system cleanliness (the bottom-up approach) ..	6
6.1	Principles	6
6.2	Determination of the cleanliness level of a component	6
6.3	Prediction of cleanliness level of an assembled system	7
6.4	Prediction of cleanliness level of a new system upon its release from the manufacturing area	7
6.5	Practical predictions	8
7	Specifying the cleanliness requirements from system cleanliness level to component cleanliness level (the top-down approach)	9
7.1	Principle	9
7.2	Specification of identical requirements	9
7.3	Specification of different requirements	9
8	Relationship between cleanliness levels per unit volume and cleanliness levels per unit surface area	10
8.1	V/A ratio	10
8.2	Impact of surface cleanliness level on fluid cleanliness level	10
Annex A (informative) Determination of geometrical characteristics of components		11
Annex B (informative) Example of calculation of the cleanliness of an assembled system from the cleanliness of individual components		12
Annex C (informative) Impact of surface cleanliness level on fluid cleanliness level		17
Annex D (informative) Relating volume to surface area		20
Annex E (informative) Relating the cleanliness of parts to the cleanliness of components		21
Bibliography		24