

# ISO 10300-2:2014-04 (E)

## Calculation of load capacity of bevel gears - Part 2: Calculation of surface durability (pitting)

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
Introduction .....		v
1	Scope .....	1
2	Normative references .....	1
3	Terms and definitions .....	1
4	Symbols, units and abbreviated terms .....	2
5	Pitting damage -- General aspects .....	3
5.1	Acceptable versus unacceptable pitting .....	3
5.2	Assessment requirements .....	3
5.3	General rating procedure .....	4
6	Gear flank rating formulae -- Method B1 .....	4
6.1	Contact stress formula .....	4
6.2	Permissible contact stress .....	6
6.3	Calculated safety factor for contact stress .....	6
6.4	Contact stress factors .....	6
6.5	Permissible contact stress factors .....	10
7	Gear flank rating formulae -- Method B2 .....	13
7.1	Contact stress formula .....	13
7.2	Permissible contact stress .....	14
7.3	Calculated safety factor for contact stress .....	14
7.4	Contact stress factors .....	15
8	Factors for contact stress and permissible contact stress common for method B1 and method B2 .....	20
8.1	Elasticity factor, $Z_E$ .....	20
8.2	Lubricant film influence factors, $Z_L$ , $Z_V$ , $Z_R$ .....	20
8.3	Work hardening factor, $Z_W$ .....	24
8.4	Life factor, $Z_{NT}$ .....	25
Annex A (informative)	Bevel slip factor $Z_S$ -- Method B1 .....	28
Bibliography .....		30