

# ISO 6358-3:2014-10 (E)

## Pneumatic fluid power - Determination of flow-rate characteristics of components using compressible fluids - Part 3: Method for calculating steady-state flow-rate characteristics of systems

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
Introduction .....		v
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>1</b>
<b>4</b>	<b>Symbols and units .....</b>	<b>1</b>
<b>5</b>	<b>Calculation hypotheses .....</b>	<b>2</b>
<b>5.1</b>	<b>General .....</b>	<b>2</b>
<b>5.2</b>	<b>Relationships among component flow-rate characteristics .....</b>	<b>3</b>
<b>5.3</b>	<b>Flow-rate characteristics .....</b>	<b>3</b>
<b>6</b>	<b>Organization of calculations for systems of components connected in series .....</b>	<b>6</b>
<b>6.1</b>	<b>General .....</b>	<b>6</b>
<b>6.2</b>	<b>Given parameters .....</b>	<b>7</b>
<b>6.3</b>	<b>Calculation principle .....</b>	<b>7</b>
<b>6.4</b>	<b>Calculation of the cracking pressure <math>p_c</math> (step 1) .....</b>	<b>7</b>
<b>6.5</b>	<b>Calculation of an initial value for their sonic conductance if some components are pipes, tubes or hoses defined by their friction factor (optional step 2) .....</b>	<b>7</b>
<b>6.6</b>	<b>Determination of the sonic conductance <math>C</math> (step 3) .....</b>	<b>8</b>
<b>6.7</b>	<b>Determining the critical back-pressure ratio <math>b</math> and subsonic index <math>m</math> (step 4) .....</b>	<b>10</b>
<b>6.8</b>	<b>Calculation of pressure dependence coefficient <math>K_p</math> (optional step 5) .....</b>	<b>11</b>
<b>7</b>	<b>Organization of calculations for systems of components connected in parallel .....</b>	<b>12</b>
<b>7.1</b>	<b>General .....</b>	<b>12</b>
<b>7.2</b>	<b>Given parameters .....</b>	<b>12</b>
<b>7.3</b>	<b>Calculation principle .....</b>	<b>12</b>
<b>7.4</b>	<b>Determination of flow characteristics of pipes, tubes or hoses for the given inlet pressure (step 0) .....</b>	<b>13</b>
<b>7.5</b>	<b>Determination of the sonic conductance <math>C</math> (step 1) .....</b>	<b>13</b>
<b>7.6</b>	<b>Determination of the cracking pressure <math>p_c</math> (step 2) .....</b>	<b>13</b>
<b>7.7</b>	<b>Determination of the critical back-pressure ratio <math>b</math> and subsonic index <math>m</math> (step 3) .....</b>	<b>13</b>
	<b>Annex A (informative) Example calculation for a system of components connected in series .....</b>	<b>15</b>
	<b>Annex B (informative) Example calculation for an air blow circuit whose components are connected in parallel .....</b>	<b>25</b>
	<b>Annex C (informative) Flow charts of calculation procedures .....</b>	<b>32</b>
	<b>Annex D (informative) Additional information concerning components whose flow rate characteristics are not expressed in accordance with the ISO 6358 series .....</b>	<b>41</b>
	<b>Annex E (informative) Visualization of calculation results .....</b>	<b>53</b>
	<b>Bibliography .....</b>	<b>59</b>