

# ISO/TR 15144-2:2014-10 (E)

## Calculation of micro-pitting load capacity of cylindrical spur and helical gears - Part 2: Examples of calculation for micropitting

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
Introduction .....		v
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms, definitions, symbols, and units .....</b>	<b>1</b>
<b>3.1</b>	<b>Terms and definitions .....</b>	<b>1</b>
<b>3.2</b>	<b>Symbols and units .....</b>	<b>1</b>
<b>4</b>	<b>Example calculation .....</b>	<b>4</b>
<b>4.1</b>	<b>Example 1 -- Spur gear .....</b>	<b>5</b>
<b>4.1.1</b>	<b>Input data .....</b>	<b>6</b>
<b>4.1.2</b>	<b>Calculation according to method B .....</b>	<b>7</b>
<b>4.1.3</b>	<b>Calculation according to method A .....</b>	<b>12</b>
<b>4.1.4</b>	<b>Calculation of the permissible lubricant film thickness .....</b>	<b>13</b>
<b>4.2</b>	<b>Example 2 -- Spur gear .....</b>	<b>19</b>
<b>4.2.1</b>	<b>Input data .....</b>	<b>20</b>
<b>4.2.2</b>	<b>Calculation according to method B .....</b>	<b>21</b>
<b>4.3</b>	<b>Example 3 -- Helical gear .....</b>	<b>28</b>
<b>4.3.1</b>	<b>Input data .....</b>	<b>29</b>
<b>4.3.2</b>	<b>Calculation according to method B .....</b>	<b>30</b>
<b>4.3.3</b>	<b>Calculation according to method A .....</b>	<b>36</b>
<b>4.4</b>	<b>Example 4 -- Speed increaser .....</b>	<b>37</b>
<b>4.4.1</b>	<b>Input data .....</b>	<b>38</b>
<b>4.4.2</b>	<b>Calculation according to method B .....</b>	<b>39</b>
<b>4.4.3</b>	<b>Calculation according to method A .....</b>	<b>45</b>
<b>Bibliography .....</b>		<b>47</b>