

ISO 16122-4:2015-03 (E)

Agricultural and forestry machines - Inspection of sprayers in use - Part 4: Fixed and semi-mobile sprayers

| Contents | | Page |
|---------------------------|----------------------------------------------------------------------------------------------------------------|-------------|
| 4.11.2 | Travel speed spray robots | 11 |
| 4.12 | Cleaning equipment | 12 |
| 5 | Test methods | 12 |
| 5.1 | Test facilities | 12 |
| 5.2 | Spray and agitation pump(s) | 12 |
| 5.2.1 | Pump capacity test | 12 |
| 5.2.2 | Pump pulsations | 14 |
| 5.3 | Sprayer pressure indicators | 14 |
| 5.3.1 | Specifications of pressure indicators used for verification | 14 |
| 5.3.2 | Verification method of the sprayer pressure indicator | 15 |
| 5.4 | Flow meters for controlling the volume/hectare rate | 15 |
| 5.4.1 | General | 15 |
| 5.4.2 | Operating procedure No.1: Verification by nozzle flow rate measurement | 15 |
| 5.4.3 | Operating procedure No.2: Verification by installing a standard flow meter on the circuit of the sprayer | 15 |
| 5.5 | System for controlling forward speed | 15 |
| 5.6 | Uniformity of the transverse volume distribution with a horizontal patternator | 15 |
| 5.6.1 | Specification of horizontal patternators used for verification | 15 |
| 5.6.2 | Calculation of the coefficient of variation (CV) | 16 |
| 5.6.3 | Verification method of the uniformity of the transverse distribution | 16 |
| 5.7 | Flow rate of the spray nozzles | 17 |
| 5.7.1 | General | 17 |
| 5.7.2 | Measurement with nozzles fitted on the sprayer | 17 |
| 5.7.3 | Measurement with nozzles removed from the sprayer | 17 |
| 5.8 | Pressure drop | 17 |
| 5.9 | Pressure variation when the sections are closed | 17 |
| 5.10 | Pressure variation when the spray is switched off | 17 |
| 5.11 | Accuracy of direct injection systems | 18 |
| 5.12 | Pressure distribution | 18 |
| Bibliography | | 19 |