

ISO 16122-4:2015-03 (E)

Agricultural and forestry machines - Inspection of sprayers in use - Part 4: Fixed and semi-mobile sprayers

Contents		Page
4.11.2	Travel speed spray robots	11
4.12	Cleaning equipment	12
5	Test methods	12
5.1	Test facilities	12
5.2	Spray and agitation pump(s)	12
5.2.1	Pump capacity test	12
5.2.2	Pump pulsations	14
5.3	Sprayer pressure indicators	14
5.3.1	Specifications of pressure indicators used for verification	14
5.3.2	Verification method of the sprayer pressure indicator	15
5.4	Flow meters for controlling the volume/hectare rate	15
5.4.1	General	15
5.4.2	Operating procedure No.1: Verification by nozzle flow rate measurement	15
5.4.3	Operating procedure No.2: Verification by installing a standard flow meter on the circuit of the sprayer	15
5.5	System for controlling forward speed	15
5.6	Uniformity of the transverse volume distribution with a horizontal patternator	15
5.6.1	Specification of horizontal patternators used for verification	15
5.6.2	Calculation of the coefficient of variation (CV)	16
5.6.3	Verification method of the uniformity of the transverse distribution	16
5.7	Flow rate of the spray nozzles	17
5.7.1	General	17
5.7.2	Measurement with nozzles fitted on the sprayer	17
5.7.3	Measurement with nozzles removed from the sprayer	17
5.8	Pressure drop	17
5.9	Pressure variation when the sections are closed	17
5.10	Pressure variation when the spray is switched off	17
5.11	Accuracy of direct injection systems	18
5.12	Pressure distribution	18
	Bibliography	19