

ISO 8812:2016-04 (E)

Earth-moving machinery - Backhoe loaders - Terminology and commercial specifications

| Contents | | Page |
|-----------------|---|-------------|
| Foreword | | iv |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 1 |
| 4 | Base machine | 2 |
| 4.1 | Types of backhoe loaders | 2 |
| 4.2 | Dimensions | 6 |
| 4.2.1 | Operational positions of backhoe | 8 |
| 4.2.2 | Operational position of stabilizers and outriggers | 9 |
| 4.2.3 | Manoeuvring dimensions | 10 |
| 4.3 | Nomenclature | 11 |
| 5 | Attachment (tool) nomenclature | 14 |
| 6 | Performance terminology | 14 |
| 6.1 | General | 14 |
| 6.1.1 | ISO net power (engine) | 14 |
| 6.1.2 | Maximum travel speeds | 14 |
| 6.1.3 | Braking performance | 15 |
| 6.1.4 | Steering capability | 15 |
| 6.1.5 | Turning radius | 15 |
| 6.2 | Loader operation | 15 |
| 6.2.1 | Rated operating load | 15 |
| 6.2.2 | Breakout force | 15 |
| 6.2.3 | Tipping load | 15 |
| 6.2.4 | Tipping load at specified height | 15 |
| 6.2.5 | Raising time | 15 |
| 6.2.6 | Lowering time | 15 |
| 6.2.7 | Dump time | 15 |
| 6.3 | Backhoe operation | 15 |
| 6.3.1 | Maximum hoe tool force using bucket cylinders | 15 |
| 6.3.2 | Maximum hoe tool force using arm cylinders | 15 |
| 7 | Commercial literature specifications -- SI units (examples) | 16 |
| 7.1 | Engine | 16 |
| 7.2 | Transmission | 16 |
| 7.3 | Drive axles | 16 |
| 7.4 | Steering | 17 |
| 7.5 | Brakes | 17 |
| 7.5.1 | Service brake | 17 |
| 7.5.2 | Parking brake | 17 |
| 7.5.3 | Secondary brake | 17 |
| 7.5.4 | Brake performance | 17 |
| 7.6 | Tyres and rims | 18 |
| 7.7 | Hydraulic system | 18 |
| 7.8 | System fluid capacities | 18 |
| 7.9 | Masses | 18 |

| | | |
|-------------|---|-----------|
| 7.10 | Filtration system (type) | 18 |
| 7.11 | Characteristics which can be affected by bucket selection (machine equipped with non-standard tyres) | 19 |
| | Annex A (normative) Base machine -- Dimensions -- Symbols, terms and definitions | 20 |
| | Bibliography | 26 |