ISO 18063-1:2016-11 (E)

Rough-terrain trucks - Visibility - Test methods and their verification - Part 1: Variable-reach trucks

Contents

Page

Foreword iv

Introduction v

1 Scope 1

2 Normative references 1

3 Terms and definitions 1

4 Test apparatus 5
4.1 Light source apparatus 5
4.2 Vertical test object 5
4.3 Observation mirror 5

5 Truck test configuration 5
5.1 Equipment of the truck 5
5.2 Openings 6
5.3 Position of the truck and load handling attachment 6

6 Measurement procedure 6
6.1 Test-surface marking and truck location on the test surface 6
6.2 Positioning of the test apparatus 7
6.3 Measurements of the maskings 8
6.3.1 General 8
6.3.2 Measurement at the visibility test circle 8
6.3.3 Measurement at the rectangular 1 m boundary 9
6.4 Requirements for derivative trucks 10

7 Evaluation method and performance criteria 10
7.1 Visibility performance criteria on the visibility test circle 10
7.2 Visibility performance criteria for the rectangular 1 m boundary 10
7.3 Visibility maskings that exceed the visibility performance criteria with direct view 10

8 Calculation method and computer simulation 10

9 Test report 10
9.1 Truck details 10
9.2 Drawing 11

10 Information for use 11

Annex A (informative) Light source spacing dimensions 13

Annex B (informative) Performance criteria for additional devices 14

Annex C (informative) Procedure for the determination of maskings at the visibility test circle or the rectangular 1 m boundary 15

Annex D (informative) Examples of drawings for the test report 16

Bibliography 17