

DIN EN 16770:2018-12 (E)

Safety of woodworking machines - Chip and dust extraction systems for indoor installation - Safety requirements

Contents		Page
European foreword		4
Introduction		5
1	Scope	6
2	Normative references	6
3	Terms, definitions, symbols and units	7
3.1	Terms and definitions	7
3.2	Symbols and units	10
4	List of significant hazards	10
5	Safety requirements and/or measures	12
5.1	General	12
5.2	Control systems	12
5.2.1	Safety and reliability of control systems	12
5.2.2	Emergency stop	13
5.2.3	Fan start/stop	13
5.3	Protection against mechanical hazards	14
5.3.1	Shearing, crushing, drawing-in	14
5.3.2	Pneumatics	14
5.3.3	Stability	14
5.4	Protection against fire	14
5.4.1	Avoidance of effective ignition sources	14
5.4.2	Avoidance of material accumulation in ducting	15
5.4.3	Measures against fire spreading	15
5.5	Noise	16
5.5.1	Noise reduction at the design stage	16
5.5.2	Noise emission measurement	17
5.6	Protection against hazardous substances	17
5.6.1	Dust emissions	17
5.6.2	Performance requirements	17
5.6.3	Performance indication	18
5.7	Protection against electrical hazards	18
5.8	Ergonomics	19
5.9	Isolation	19
6	Information for use	19
6.1	General	19
6.2	Marking	19
6.3	Instruction handbook	20
6.3.1	General	20
6.3.2	Information related to installation	21
6.3.3	Information related to operation	21
6.3.4	Information related to maintenance	22
6.3.5	Noise declaration	22
Annex A (normative) Types of dust extractors		24

Annex B (normative) Active ignition source detection and suppression system	26
Annex C (normative) Fire suppression system	28
Annex D (informative) Noise reduction at the design stage	29
D.1 General	29
D.2 Noise sources	29
D.3 Measures to reduce noise	29
D.4 Impacts from chips and dust	30
Annex E (normative) Measurement of vacuum, cleaning interval and residual dust content	31
Annex F (informative) Interface to woodworking machinery	32
Annex ZA (informative) Relationship between this European Standard and the essential requirements of Directive 2006/42/EC aimed to be covered	33
Bibliography	36