

# DIN EN 16842-2:2018-10 (E)

## Powered industrial trucks - Visibility - Test methods and verification - Part 2: Sit-on counterbalance trucks and rough terrain masted trucks up to and including 10 000 kg capacity

---

| <b>Contents</b>  |   | <b>Page</b> |
|--|---|-------------|
| European foreword .....  |   | 3           |
| Introduction .....   |   | 5           |
| 1  | Scope .....   | 6           |
| 2  | Normative references .....  | 6           |
| 3  | Terms and definitions .....   | 6           |
| 4  | Truck configuration .....   | 6           |
| 4.1  | General .....   | 6           |
| 4.2  | Fork arm dimensions .....   | 6           |
| 5  | Test equipment .....  | 7           |
| 6  | Test procedures for direct visibility .....   | 7           |
| 6.1  | Lighting equipment position .....   | 7           |
| 6.2  | Test paths for trucks < 10 000 kg .....   | 8           |
| 6.3  | Measurement procedure .....   | 9           |
| 6.4  | Test procedure for indirect visibility .....  | 9           |
| 7  | Acceptance criteria .....   | 9           |
| 7.1  | General .....   | 9           |
| 7.2  | Direct visibility .....   | 9           |
| 7.2.1  | General .....   | 9           |
| 7.2.2  | Travelling visibility .....   | 9           |
| 7.2.3  | Manoeuvring visibility .....  | 9           |
| 7.2.4  | Fork arms .....   | 9           |
| 7.3  | Indirect visibility .....   | 9           |
| 7.4  | Criteria for trucks up to and including 5 000 kg rated capacity .....               | 10          |
| 7.5  | Trucks greater than 5 000 kg and up to and including 10 000 kg rated capacity ..... | 11          |
| 8  | Test report .....   | 12          |
| 9  | Information for use .....   | 12          |
| Annex A (informative) Information for operator visibility during use ..... |   | 13          |
| A.1  | General .....   | 13          |
| A.2  | Method 1 .....  | 14          |
| A.3  | Method 2 .....  | 15          |
| Bibliography .....   |   | 16          |