ISO 5006:2017-04 (E)

Earth-moving machinery - Operator's field of view - Test method and performance criteria

Contents

Page

Foreword iv

Introduction v

1 Scope 1

2 Normative references 1

3 Terms and definitions 1

4 Basic dimensions 5
4.1 Light spacing dimensions 5
4.2 Masking dimensions 5
4.3 Reference dimensions for measurement purposes 5

5 Test apparatus 5

6 Machine test configuration 6

7 Performance criteria for indirect visibility 6
7.1 Visibility aids 6
7.2 Position of display devices 6
7.3 Performance criteria for mirrors 6
7.4 Performance criteria for CCTV system 7

8 Measurement procedure 7
8.1 Test-surface marking and machine location on test surface 7
8.2 Positioning of test apparatus 7
8.3 Measurement of maskings 8
8.3.1 General 8
8.3.2 Measurement at the VTC 9
8.3.3 Measurement at RB 9

9 Calculation method 11
9.1 Calculation procedure for determining maskings at VTC or RB 11
9.2 Computer-simulation 12

10 Evaluation method and performance criteria 12
10.1 Visibility performance criteria on VTC 12
10.2 Visibility performance criteria for RB 17
10.3 Visibility maskings that exceed visibility performance criteria with direct view 18
10.4 Requirements for larger, derivative and other types of earth-moving machinery not covered in Table 1 and Table 2 19
10.4.1 Larger machines 19
10.4.2 Derivative and other types of earth-moving machinery 20
10.4.3 Risk assessment process for larger, derivative or other types of earth- moving machinery not covered in Table 1 and Table 2 20
10.4.4 Visibility test circle and allowed masking width 20

11 Test report 20
11.1 Machine details 20

11.2 Drawing 21

12 Visibility information for operator's manual 21

Annex A (normative) Dimensions and position of HH and rectangular boundary (RB) 22

Bibliography 29