

ISO 5006:2017-04 (E)

Earth-moving machinery - Operator's field of view - Test method and performance criteria

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Basic dimensions	5
4.1	Light spacing dimensions	5
4.2	Masking dimensions	5
4.3	Reference dimensions for measurement purposes	5
5	Test apparatus	5
6	Machine test configuration	6
7	Performance criteria for indirect visibility	6
7.1	Visibility aids	6
7.2	Position of display devices	6
7.3	Performance criteria for mirrors	6
7.4	Performance criteria for CCTV system	7
8	Measurement procedure	7
8.1	Test-surface marking and machine location on test surface	7
8.2	Positioning of test apparatus	7
8.3	Measurement of maskings	8
8.3.1	General	8
8.3.2	Measurement at the VTC	9
8.3.3	Measurement at RB	9
9	Calculation method	11
9.1	Calculation procedure for determining maskings at VTC or RB	11
9.2	Computer-simulation	12
10	Evaluation method and performance criteria	12
10.1	Visibility performance criteria on VTC	12
10.2	Visibility performance criteria for RB	17
10.3	Visibility maskings that exceed visibility performance criteria with direct view	18
10.4	Requirements for larger, derivative and other types of earth-moving machinery not covered in Table 1 and Table 2	19
10.4.1	Larger machines	19
10.4.2	Derivative and other types of earth-moving machinery	20
10.4.3	Risk assessment process for larger, derivative or other types of earth-moving machinery not covered in Table 1 and Table 2	20
10.4.4	Visibility test circle and allowed masking width	20
11	Test report	20
11.1	Machine details	20

11.2	Drawing	21
12	Visibility information for operator's manual	21
Annex A (normative)	Dimensions and position of HH and rectangular boundary (RB)	22
Bibliography		29