ISO 5682-2:2017-05 (E)

Equipment for crop protection - Spraying equipment - Part 2: Test methods to assess the horizontal transverse distribution for hydraulic sprayers

Contents

Page

Foreword iv

1 Scope 1

2 Normative references 1

3 Termsanddefinitions 1

4 Measuring equipment 1

5 Test conditions 2
5.1 General 2
5.2 Temperature and relative humidity 2
5.3 Choice of nozzles for the tests 2
5.4 Control pressure 2

6 Test methods 2
6.1 General 2
6.2 Standard conditions 3
6.3 Transverse distribution evaluation by means of sprayed liquid volume measurement - sprayed liquid volume measurement method 3
6.3.1 Setup 3
6.3.2 Measurement 3
6.3.3 Results 4
6.4 Nozzle tip position 4
6.4.1 Spacing 4
6.4.2 Alignment 4
6.5 Transverse distribution evaluation by means of nozzle flow rate measurement - nozzle flow rate measurement test method 4
6.5.1 Setup 4
6.5.2 Measurements 5
6.5.3 Results 5
6.6 Transverse distribution evaluation by means of nozzle tip pressure measurement - nozzle tip pressure measurement test method 5
6.6.1 Setup 5
6.6.2 Measurements 6
6.6.3 Results 6

Annex A (informative) Transverse distribution test report 7

Annex B (informative) Applicable test methods 9

Annex C (informative) Guidance to estimate horizontal transverse distribution 10