

ISO 5682-2:2017-05 (E)

Equipment for crop protection - Spraying equipment - Part 2: Test methods to assess the horizontal transverse distribution for hydraulic sprayers

Contents	Page
Foreword	iv
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Measuring equipment	1
5 Test conditions	2
5.1 General	2
5.2 Temperature and relative humidity	2
5.3 Choice of nozzles for the tests	2
5.4 Control pressure	2
6 Test methods	2
6.1 General	2
6.2 Standard conditions	3
6.3 Transverse distribution evaluation by means of sprayed liquid volume measurement - sprayed liquid volume measurement method	3
6.3.1 Setup	3
6.3.2 Measurement	3
6.3.3 Results	4
6.4 Nozzle tip position	4
6.4.1 Spacing	4
6.4.2 Alignment	4
6.5 Transverse distribution evaluation by means of nozzle flow rate measurement - nozzle flow rate measurement test method	4
6.5.1 Setup	4
6.5.2 Measurements	5
6.5.3 Results	5
6.6 Transverse distribution evaluation by means of nozzle tip pressure measurement - nozzle tip pressure measurement test method	5
6.6.1 Setup	5
6.6.2 Measurements	6
6.6.3 Results	6
Annex A (informative) Transverse distribution test report	7
Annex B (informative) Applicable test methods	9
Annex C (informative) Guidance to estimate horizontal transverse distribution	10