ISO 3968:2017-07 (E)

Hydraulic fluid power - Filters - Evaluation of differential pressure versus flow

Contents

Page

Foreword iv

Introduction v

1 Scope 1

2 Normative references 1

3 Terms and definitions 1

4 Symbols 2
4.1 Letter symbols 2
4.2 Graphical symbols 2

5 Operational characteristics to be tested 2

6 Filter to be tested 3
6.1 Filter type 3
6.2 Filter element 3

7 Test equipment 3
7.1 General indications 3
7.2 Pump 3
7.3 Reservoir 3
7.4 Temperature control 4
7.5 Clean-up filter 4
7.6 Sampling valve 4
7.7 Mounting of filter 5
7.8 Test fluid 6

8 Measurements 6
8.1 Pressure measurement 6
8.2 Temperature measurement 8
8.3 Kinematic viscosity measurement 8
8.4 Flow rate measurement 9
8.5 Fluid cleanliness measurement 9
8.6 Accuracy of measuring instruments and test conditions 9

9 Procedure 9
9.1 Pipework correction 9
9.2 Cleanliness of test circuit 9
9.3 Characteristics of the filter housing (filter type 6.1.3) 10
9.4 Characteristics of the filter assembly (filter type 6.1.3) 10
9.5 Characteristics of the filter element only (filter type 6.1.3) 10
9.6 Characteristics of the head and spin-on (filter type 6.1.2) 10
9.7 Characteristics of the spin-on (filter type 6.1.1) 11
9.8 Characteristics of the bypass valve 11
9.8.1 Preliminary installation 11
9.8.2 Determination of full flow rate characteristics 11
9.8.3 Determination of opening pressure 11
9.8.4 Determination of closing pressure 12
9.8.5 Measurement of leakage rate 12

10 Presentation of results 12

11 Identification statement (reference to this document) 14

Annex A (informative) Introduction to the power loss equation and method to calculate 15

Bibliography 17