

# ISO 3968:2017-07 (E)

## Hydraulic fluid power - Filters - Evaluation of differential pressure versus flow

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
Introduction .....		v
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>1</b>
<b>4</b>	<b>Symbols .....</b>	<b>2</b>
<b>4.1</b>	<b>Letter symbols .....</b>	<b>2</b>
<b>4.2</b>	<b>Graphical symbols .....</b>	<b>2</b>
<b>5</b>	<b>Operational characteristics to be tested .....</b>	<b>2</b>
<b>6</b>	<b>Filter to be tested .....</b>	<b>3</b>
<b>6.1</b>	<b>Filter type .....</b>	<b>3</b>
<b>6.2</b>	<b>Filter element .....</b>	<b>3</b>
<b>7</b>	<b>Test equipment .....</b>	<b>3</b>
<b>7.1</b>	<b>General indications .....</b>	<b>3</b>
<b>7.2</b>	<b>Pump .....</b>	<b>3</b>
<b>7.3</b>	<b>Reservoir .....</b>	<b>3</b>
<b>7.4</b>	<b>Temperature control .....</b>	<b>4</b>
<b>7.5</b>	<b>Clean-up filter .....</b>	<b>4</b>
<b>7.6</b>	<b>Sampling valve .....</b>	<b>4</b>
<b>7.7</b>	<b>Mounting of filter .....</b>	<b>5</b>
<b>7.8</b>	<b>Test fluid .....</b>	<b>6</b>
<b>8</b>	<b>Measurements .....</b>	<b>6</b>
<b>8.1</b>	<b>Pressure measurement .....</b>	<b>6</b>
<b>8.2</b>	<b>Temperature measurement .....</b>	<b>8</b>
<b>8.3</b>	<b>Kinematic viscosity measurement .....</b>	<b>8</b>
<b>8.4</b>	<b>Flow rate measurement .....</b>	<b>9</b>
<b>8.5</b>	<b>Fluid cleanliness measurement .....</b>	<b>9</b>
<b>8.6</b>	<b>Accuracy of measuring instruments and test conditions .....</b>	<b>9</b>
<b>9</b>	<b>Procedure .....</b>	<b>9</b>
<b>9.1</b>	<b>Pipework correction .....</b>	<b>9</b>
<b>9.2</b>	<b>Cleanliness of test circuit .....</b>	<b>9</b>
<b>9.3</b>	<b>Characteristics of the filter housing (filter type 6.1.3) .....</b>	<b>10</b>
<b>9.4</b>	<b>Characteristics of the filter assembly (filter type 6.1.3) .....</b>	<b>10</b>
<b>9.5</b>	<b>Characteristics of the filter element only (filter type 6.1.3) .....</b>	<b>10</b>
<b>9.6</b>	<b>Characteristics of the head and spin-on (filter type 6.1.2) .....</b>	<b>10</b>
<b>9.7</b>	<b>Characteristics of the spin-on (filter type 6.1.1) .....</b>	<b>11</b>
<b>9.8</b>	<b>Characteristics of the bypass valve .....</b>	<b>11</b>
<b>9.8.1</b>	<b>Preliminary installation .....</b>	<b>11</b>
<b>9.8.2</b>	<b>Determination of full flow rate characteristics .....</b>	<b>11</b>
<b>9.8.3</b>	<b>Determination of opening pressure .....</b>	<b>11</b>
<b>9.8.4</b>	<b>Determination of closing pressure .....</b>	<b>12</b>
<b>9.8.5</b>	<b>Measurement of leakage rate .....</b>	<b>12</b>

<b>10</b>	<b>Presentation of results .....</b>	<b>12</b>
<b>11</b>	<b>Identification statement (reference to this document) .....</b>	<b>14</b>
	<b>Annex A (informative) Introduction to the power loss equation and method to calculate .....</b>	<b>15</b>
	<b>Bibliography .....</b>	<b>17</b>