DIN ISO 15171-2:2017-12 (E)

Connections for fluid power and general use - Hydraulic couplings for diagnostic pur poses - Part 2: Coupling with M16 x 2 end for connection under pressure (ISO 15171-2:2016)

Contents

Page

National foreword 3

Foreword 4

Introduction 5

1 Scope 6

2 Normative references 6

3 Terms and definitions 7

4 Performance requirements 7
4.1 General 7
4.2 Working pressure and temperature 7
4.3 Flow rate and pressure drop 7
4.4 Connection of the coupling with a coupling counterpart 7
4.5 Burst and cyclic endurance (impulse) test pressures 8
4.6 Test requirements 8

5 Design 8
5.1 Basic dimensions 8
5.2 Diagnostic coupling with a stud end ISO 6149-2, M14 × 1,5 10
5.3 Diagnostic coupling with a stud end ISO 9974-2, M14 × 1,5 10
5.4 Diagnostic coupling with a stud end ISO 1179-2, G1/4 10
5.5 Diagnostic coupling with a stud end ISO 11926-2, 7/16-20 UNF 11

6 Manufacture 11
6.1 Construction 11
6.2 Workmanship 11
6.3 Finish 12

7 Designation of couplings 12

8 Marking 12

9 Identification statement (reference to this part of ISO 15171) 12

Annex A (informative) Other hydraulic connection types suitable for diagnostic couplings 13

A.1 General 13
A.2 Diagnostic couplings with straight union connectors 13
A.3 Diagnostic couplings with swivel connector ends 13

Bibliography 14