

DIN ISO 15171-2:2017-12 (E)

Connections for fluid power and general use - Hydraulic couplings for diagnostic purposes - Part 2: Coupling with M16 x 2 end for connection under pressure (ISO 15171-2:2016)

Contents		Page
National foreword		3
Foreword		4
Introduction		5
1	Scope	6
2	Normative references	6
3	Terms and definitions	7
4	Performance requirements	7
4.1	General	7
4.2	Working pressure and temperature	7
4.3	Flow rate and pressure drop	7
4.4	Connection of the coupling with a coupling counterpart	7
4.5	Burst and cyclic endurance (impulse) test pressures	8
4.6	Test requirements	8
5	Design	8
5.1	Basic dimensions	8
5.2	Diagnostic coupling with a stud end ISO 6149-2, M14 × 1,5	10
5.3	Diagnostic coupling with a stud end ISO 9974-2, M14 × 1,5	10
5.4	Diagnostic coupling with a stud end ISO 1179-2, G1/4	10
5.5	Diagnostic coupling with a stud end ISO 11926-2, 7/16-20 UNF	11
6	Manufacture	11
6.1	Construction	11
6.2	Workmanship	11
6.3	Finish	12
7	Designation of couplings	12
8	Marking	12
9	Identification statement (reference to this part of ISO 15171)	12
Annex A (informative)	Other hydraulic connection types suitable for diagnostic couplings	13
A.1	General	13
A.2	Diagnostic couplings with straight union connectors	13
A.3	Diagnostic couplings with swivel connector ends	13
Bibliography		14